

# IKO Ultra T-O Underlay

## Technical Data Sheet – Section 5.20

### PRODUCT INFORMATION

IKO Ultra T-O Underlay is a fully bonded torch-applied, polyester reinforced, SBS modified bitumen underlay. It has an upper surface finish of sand and a thermo-fusible film on the underside.

Surface	Product Code
Sand	62150000

### USE

This product is for use as an underlay within an IKO high-performance built-up roofing system specification.

The product must be applied by an IKO Approved Installer.

All work must be undertaken in accordance with the requirements of the specific information provided with the issued IKO Specification document, or guidance documents where applicable.

As this product is utilised within an Approved Contractor network and guided by an IKO Specification document, where omission or differing information exists the IKO Specification document will take precedence.



### INDEPENDENT ACCREDITATION



2797-CPR-537586



0086-CPR-745786

The product carries a Declaration of Performance Certificate and is UK Conformity Assessed.

### COMPOSITION

Bitumen Modification:	SBS
Carrier:	Polyester
Form:	Roll
Colour:	Sanded
Length:	12m
Width:	1m
Mass/Weight:	3.167kg/m <sup>2</sup>
Roll Weight:	38kg
Surface Finishes:	(upper) Sand (lower) Thermo-fusible film
Selvage:	(upper) 75mm

## INSTALLATION

Membrane Bond: Torch applied  
Lap Bond: Torch applied

## OTHER RELEVANT DOCUMENTATION

Where applicable, Material Safety Data Sheets (MSDS), Declaration of Performances (DoPs), and Third-Party Accreditations are available to view and download from the IKO website Resource Centre:

<https://ikogroup.co.uk/resource-centre/>

## PRODUCT SUPPORT

Should you have any queries in relation to this product please contact one of the relevant teams below:

**Technical** [technical.ab@iko.com](mailto:technical.ab@iko.com)  
- For Reinforced Bitumen Membranes, IKOpro and Flexia Liquid Applied Waterproofing, Pitched Roofing, IKO Hyload Structural Waterproofing  
[technical.ma@iko.com](mailto:technical.ma@iko.com)  
- For Mastic Asphalt  
[technical.cc@iko.com](mailto:technical.cc@iko.com)  
- For Single Ply and Permateg Hot Melt

**Sales** [sales.uk@iko.com](mailto:sales.uk@iko.com)

**Marketing** [getintouch.uk@iko.com](mailto:getintouch.uk@iko.com)

## COMPANY ACCREDITATIONS

IKO PLC, a roofing, waterproofing, and insulation company, holds various accreditations that demonstrate its commitment to quality, safety, and environmental responsibility. These include ISO certifications for quality management and occupational health and safety, British Board of Agrément (BBA) accreditations for specific products and systems, and Factory Mutual (FM) approval for certain roofing systems.

All our manufacturing plants have BS EN ISO 9001, BS EN ISO 14001, BS EN ISO 45001, BES 6001, and PAS 2080 accreditation, meaning we match the quality and sustainability requirements and use responsibly sourced raw materials in our production. We also re-use by-products from manufacture, wrap products in minimal packaging, and we employ a streamlined transportation network.



IKO is also a leading member of all relevant trade associations such as NFRC, BFRA, SPRA, LRWA, MAC, RSTA, BJA and LCRIG having technical experts within the technical and standards committees to help us get informed first-hand about recent updates on technical requirements for the design and installation of roofing, waterproofing, road and bridge maintenance industry products.





## **DISCLAIMER**

Whilst every precaution is taken to ensure that the information given in this literature is correct and up-to-date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserves the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was published.