



Notified Body No 0836
British Board of Agrément
Bucknalls Lane
Watford
Hertfordshire WD25 9BA
Telephone: 01923 665300
Facsimile: 01923 665301
e-mail: clientservices@bbacerts.co.uk
website: www.bbacerts.co.uk

Certificate of Conformity of the Factory Production Control 0836-CPR-14/F082

In compliance with the *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this Certificate applies to the construction product:

Mastic Asphalt Paving

Permapark, Permatrack Bridge Surfacing, Gritted Paving, Pavestar, Pacopatch, Flexiphalte Pompav
Waterproofing System. Mastic Asphalt for use on roads, airfields and other trafficked areas:

Bituminous mixtures — Material specifications Part 6: Mastic Asphalt

Produced by:

IKO plc
Appley Lane North
Appley Bridge
Wigan, Lancashire
WN6 9AB

and produced in the manufacturing plant:

IKO plc
Prospect Quarry
Water Lane
Nr. Matlock
Derbyshire
DE4 4BW

This Certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s):

BS EN 13108-6 : 2016

under system 2+ for the performances set out in this Certificate are applied and that the factory production control fulfils all the prescribed requirements for these performances.

This Certificate was first issued on 25 March 2014 and remains valid for as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the factory production control certification body.

Signed on behalf of the British Board of Agrément:

Brian Moore
Operations Director

Date of Fifth issue: 18 October 2017

Annex to:

Certificate of Conformity of the Factory Production Control 0836-CPR-14/F082

**Permapark, Permatrack Bridge Surfacing, Gritted Paving, Pavestar,
Pacopatch Flexiphalte Pompav Waterproofing System. Mastic Asphalt for
use on roads, airfields and other trafficked areas:**

Bituminous mixtures — Material specifications Part 6: Mastic Asphalt

Mastic Asphalt (Permapark)

*Permapark Paving + 30% 2/6 mm Coarse Aggregate
Permapark Paving + 35% 4/10 mm Coarse Aggregate
Permapark Paving + 35% 2/6 mm Coarse Aggregate
Permapark Paving + 40% 4/10 mm Coarse Aggregate
Permapark Paving + 45% 4/10 mm Coarse Aggregate*

Mastic Asphalt (Permatrack Bridge Surfacing)

*Permatrack Bridge Surfacing + 45% 4/10 mm Agg. (MA 10 10/20)
Permatrack Bridge Surfacing + 35% 2/6 mm Agg. (MA 6 10/20)*

Mastic Asphalt (Permatrack)

*Permatrack H + 35% 2/6 Coarse Aggregate
Permatrack ICR + 35% 2/6 Coarse Aggregate
Permatrack BJ + 35% 2/6 Coarse Aggregate
Permatrack IR + 35% 2/6 Coarse Aggregate*

Mastic Asphalt (Flexiphalte Pompav) paving Layers of variants including;

*30% 2/6mm (MA 6 15/25)
35% 4/10mm (MA 10 15/25)
40% 4/10mm (MA 10 15/25)
45% 4/10mm (MA 10 15/25)*

Mastic Asphalt (Pavestar) paving Layers of variants including;

*30% Pavestar (MA 6 15/25)
35% Pavestar (MA 10 12/20)
40% Pavestar (MA 10 15/25)
45% Pavestar (MA 10 15/25)*

*T50/30% Pavestar (MA 6 15/25) — Includes 50% Trinidad Lake Asphalt (TLA)
T50/35% Pavestar (MA 10 15/25) — Includes 50% Trinidad Lake Asphalt (TLA)
T50/40% Pavestar (MA 10 15/25) — Includes 50% Trinidad Lake Asphalt (TLA)
T50/45% Pavestar (MA 10 15/25) — Includes 50% Trinidad Lake Asphalt (TLA)
T50/30% Pavestar (MA 10 9/15) — Includes 50% Trinidad Lake Asphalt (TLA)
T50/40% Pavestar (MA 10 9/15) — Includes 50% Trinidad Lake Asphalt (TLA)
T50/45% Pavestar (MA 10 9/15) — Includes 50% Trinidad Lake Asphalt (TLA)*


Mastic Asphalt

Gritted Paving MA 4 15/25

Mastic Asphalt (Pacopatch)

*Pacopatch Grout (MA 4 30/45)
Pacopatch Brick (MA 6 10/20)*

Signed on behalf of the British Board of Agrément:



Brian Moore
Operations Director