



## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product name:** IKO PRO SprayFast FMA

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** Adhesive.

### 1.3. Details of the supplier of the safety data sheet

**Company name:** IKO PLC

Appley Lane North

Appley Bridge

Wigan

Lancashire

WN6 9AB

UK

**Tel:** 01257 256779

**web:** [www.ikogroup.co.uk](http://www.ikogroup.co.uk)

### 1.4. Emergency telephone number

**Emergency tel:** +44 (0)1257 256864 Opening Times: 0900 - 1700 Monday to Friday

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Carc. 2: H351; Eye Irrit. 2: H319; Flam. Aerosol 1: H222; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 2: H371; -: EUH204

**Most important adverse effects:** Highly flammable. Irritating to eyes, respiratory system and skin. Limited evidence of a carcinogenic effect. May cause sensitisation by inhalation and skin contact. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

### 2.2. Label elements

**Label elements under CLP:**

**Hazard statements:** H222: Extremely flammable aerosol.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

IKO SPRAYFAST FMA

H351: Suspected of causing cancer .

H371: May cause damage to organs .

H373: May cause damage to organs through prolonged or repeated exposure.

EUH204: Contains isocyanates. May produce an allergic reaction.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard



**Precautionary statements:** P102: Keep out of reach of children.

P211: Do not spray on an open flame or other ignition source.

P251: Pressurized container: Do not pierce or burn, even after use.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P304+341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

**Precautionary phrases:** Contains isocyanates. See information supplied by the manufacturer.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

25 % by mass of the contents are flammable.



**Safety Data Sheet**  
**According to EC Regulation 1907/2006**  
**(REACH) & 1272/2008 (CLP) & 453/2010/**  
**Version number 1.0**

Revision: 01.06.2015

Page: 3/10

IKO Spray Fast FMA

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### DIMETHYL ETHER

EINECS	CAS	CLP Classification	Percent
204-065-8	115-10-6	Flam. Gas 1: H220; Press. Gas: H280	10-30%

##### DICHLOROMETHANE - REACH registered number(s): 01-2119480404-41-

EINECS	CAS	CLP Classification	Percent
200-838-9	75-09-2	Carc. 2: H351	10-30%

##### DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES) - REACH registered number(s): 01-2119457024-46-0006, 01-2119457024-46-0007

EINECS	CAS	CLP Classification	Percent
-	9016-87-9	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	10-30%

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove from skin with paper or towel. Wash effected area thoroughly with soap and water. Seek medical advice if symptoms persist.

**Eye contact:** Bathe the eye with running water for 15 minutes.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat. There may be shortness of breath due to congestion of the lungs.

[cont...]

IKO Spray Fast FMA

**Inhalation:** Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Alert the neighbourhood to the presence of fumes or gas. Contain the spillage using bunding.

#### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

#### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is exhaust ventilation of the area. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Ensure lighting and electrical equipment are not a source of ignition.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02mg/m <sup>3</sup>	0.07mg/m <sup>3</sup>	-	-

#### Hazardous ingredients:

##### DIMETHYL ETHER

#### Workplace exposure limits:

#### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	766 mg/m <sup>3</sup>	958 mg/m <sup>3</sup>	-	-

##### DICHLOROMETHANE

UK	350 mg/m <sup>3</sup>	1060 mg/m <sup>3</sup>	-	-
----	-----------------------	------------------------	---	---

##### DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)

UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is exhaust ventilation of the area.

**Respiratory protection:** If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

**Hand protection:** Impermeable gloves. Avoid skin contact. For repeated exposure use Viton or 4H chemical gloves. For low exposure use nitrile gloves. The user has a legal duty to carry out a COSHH risk assessment to determine the correct glove.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** No special requirement.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>State:</b>	Aerosol		
<b>Colour:</b>	Pink		
<b>Odour:</b>	Characteristic odour		
<b>Evaporation rate:</b>	Fast		
<b>Oxidising:</b>	Non-oxidising (by EC criteria)		
<b>Solubility in water:</b>	Reacts with water.		
<b>Viscosity:</b>	Non-viscous		
<b>Boiling point/range°C:</b>	>35	<b>Flash point°C:</b>	<21
<b>Relative density:</b>	1.1		

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Hot surfaces. Flames.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Toxicity values:**

Route	Species	Test	Value	Units
-------	---------	------	-------	-------

IKO Spray Fast FMA

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

**Hazardous ingredients:**

**DICHLOROMETHANE**

ORL	MUS	LD50	4770	mg/kg
ORL	RAT	LD50	5350	mg/kg
SCU	MUS	LD50	6460	mg/kg

**DIPHENYLMETHANE DIISOCYANATE (ISOMERS AND HOMOLOGUES)**

ORL	RAT	LD50	10,000	mg/kg
SKN	RBT	LD50	5,000	mg/kg

**Relevant effects for mixture:**

Effect	Route	Basis
Irritation	OPT INH DRM	Hazardous: calculated
Sensitisation	INH DRM	Hazardous: calculated
Repeated dose toxicity	INH	Hazardous: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** There may be irritation of the throat. There may be shortness of breath due to congestion of the lungs.

**Inhalation:** Exposure may cause coughing or wheezing. There may be congestion of the lungs causing severe shortness of breath.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Other information:** Not applicable.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:**

Species	Test	Value	Units
algae	NOEC	550	mg/l
fresh aquatic invertebrates	48H EC50	27	mg/l
fresh water fish	96H LC50	193	mg/l
marine aquatic invertebrates	48H EC50	109	mg/l

IKO Spray Fast FMA

marine water fish	96H LC50	97	mg/l
-------------------	----------	----	------

**12.2. Persistence and degradability****Persistence and degradability:** Biodegradable in part only.**12.3. Bioaccumulative potential****Bioaccumulative potential:** No data available.**12.4. Mobility in soil****Mobility:** Volatile.**12.5. Results of PBT and vPvB assessment****PBT identification:** This product is not identified as a PBT/vPvB substance.**12.6. Other adverse effects****Other adverse effects:** No data available.**Section 13: Disposal considerations****13.1. Waste treatment methods****Disposal operations:** Wet waste: Arrange for disposal by a licenced waste disposal company**Waste code number:** see packaging disposal**Disposal of packaging:** Ensure containers are fully empty before discarding (explosion risk) leave the discharge valve open . Risk assess and if safe to do so fully drained containers should be pierced and then disposed of inline with local regulations. USE NON SPARKING TOOL IN A FLAME PROOF AREA IF IN DOUBT TREAT AS HAZARDOUS WASTE Arrange for disposal by a licenced waste disposal company full or partial empty aerosol: 16 05 04. empty aerosol: 15 01 04 (dry- no residue) empty aerosol: 15 01 10 ( containing hazardous residues)**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**Section 14: Transport information****14.1. UN number****UN number:** UN3501**14.2. UN proper shipping name****Shipping name:** CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S  
(DIMETHYL ETHER; DICHLOROMETHANE)**14.3. Transport hazard class(es)****Transport class:** 2



IKO Spray Fast FMA

#### 14.4. Packing group

#### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

#### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** B/D

**Transport category:** 2

### Section 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** This product is classified as a mixture. CLP classification for information only. Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used

#### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

### Section 16: Other information

#### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH204: Contains isocyanates. May produce an allergic reaction.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer

H371: May cause damage to organs

H373: May cause damage to organs through prolonged or repeated exposure



**Safety Data Sheet**  
**According to EC Regulation 1907/2006**  
**(REACH) & 1272/2008 (CLP) & 453/2010/**  
**Version number 1.0**

Revision: 01.06.2015

Page: 10/10

IKO Spray Fast FMA

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

**Version History.**

Version 1.0 June 1st 2015 New release for Classification, Labelling Packaging Regulations

