



## Technical Data Sheet July 2023

### IKO Glass Fibre Tissue

#### Product Information

IKO Glass Fibre Underlay is used over concrete and cementitious substrates as a separating membrane beneath horizontal mastic asphalt flooring, paving and certain roofing applications.

It allows a free lateral passage for hot air and moisture vapour released by the substrate during the application of the hot mastic asphalt and also acts as a long term vapour release layer.

Dimensions	Roll Weight	Product Code
100m x 1m	6kg minimum	14280000
100m x 2m	12kg minimum	14290000

#### Application

IKO Glass Fibre Tissue should be loose laid with minimum 50mm side and end laps directly above the substrate.

On bituminous substrates, e.g. IKO Permascreed or contaminated surfaces, such as those with a bituminous residue, 2 layers of IKO Glass Fibre Tissue should be used to achieve the required isolation.

#### Disclaimer

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserve the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.



#### Material Handling

Please refer to the IKO Safety Data Sheet available from [www.ikogroup.co.uk](http://www.ikogroup.co.uk).