IKO Glass Fibre Tissue

Technical Data Sheet – Section 18.80

PRODUCT INFORMATION

IKO Glass Fibre Tissue is used over concrete and cementitious substrates as a separating membrane beneath horizontal mastic asphalt flooring, paving and certain roofing applications.

It allows free lateral passage for hot air and moisture vapour released by the substrate during the application of the hot mastic asphalt, and also acts as a vapour release layer in service.



OPTIONS

Dimensions	Roll Weight	Product Code
100m x 1m	6kg minimum	14280000
100m x 2m	12kg minimum	14290000

INSTALLATION

IKO Glass Fibre Tissue should be loose laid with minimum 50mm side and end laps directly above the substrate.

On bituminous substrates, e.g. IKO Permascreed or contaminated surfaces, such as those with a bituminous residue, 2 layers of IKO Glass Fibre Tissue should be used to achieve the required isolation.

OTHER RELEVENT DOCUMENTATION

Where applicable, Material Safety Data Sheets (MSDS), Declaration of Performances (DoPs), and Third-Party Accreditations are available to view and download from the IKO website Resource Centre:
https://ikogroup.co.uk/resource-centre/

PRODUCT SUPPORT

Should you have any queries in relation to this product please contact one of the relevant teams below:

Technical technical.ab@iko.com
- For Reinforced Bitumen Membranes, IKOpro and Flexia Liquid Applied Waterproofing, Pitched Roofing, IKO Hyload Structural Waterproofing

technical.ma@iko.com
- For Mastic Asphalt

technical.cc@iko.com
- For Single Ply and Permatec Hot Melt

Sales sales.uk@iko.com

Marketing getintouch.uk@iko.com

IKO PLC is a company registered in England with company no. 2678296

COMPANY ACCREDITATIONS

IKO PLC, a roofing, waterproofing, and insulation company, holds various accreditations that demonstrate its commitment to quality, safety, and environmental responsibility. These include ISO certifications for quality management and occupational health and safety, British Board of Agrément (BBA) accreditations for specific products and systems, and Factory Mutual (FM) approval for certain roofing systems.

All our manufacturing plants have BS EN ISO 9001, BS EN ISO 14001, BS EN ISO 45001, BES 6001, and PAS 2080 accreditation, meaning we match the quality and sustainability requirements and use responsibly sourced raw materials in our production. We also re-use by-products from manufacture, wrap products in minimal packaging, and we employ a streamlined transportation network.

IKO is also a leading member of all relevant trade associations such as NFRC, BFRA, SPRA, LRWA, MAC, RSTA, BJA and LCRIG having technical experts within the technical and standards committees to help us get informed first-hand about recent updates on technical requirements for the design and installation of roofing, waterproofing, road and bridge maintenance industry products.

DISCLAIMER

Whilst every precaution is taken to ensure that the information given in this literature is correct and up-to-date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserves the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was published.

IKO PLC is a company registered in England with company no. 2678296