

## IKO T-O VENTING LAYER

### PRODUCT INFORMATION

A glass fibre based perforated venting layer with a sand surface on the topside and a polyethylene film on the reverse.

Surface	Product Code
Sand	61150000

### USE

This product is specifically designed for use with torch applied roofing membranes, and when used as the first layer of a torch applied built up felt roofing system, will provide a partial bond between a non-combustible substrate and torch applied bitumen underlay.

### FEATURES & BENEFITS

**SBS and APP compatible** - product can be used with both types of bitumen modification.

**Easily installed** - loose laid prior to torch applied under layer.

### COMPOSITION

<b>Bitumen Modification:</b>	SBS
<b>Carrier:</b>	Glass Fibre
<b>Form:</b>	Roll
<b>Colour:</b>	Sanded
<b>Length:</b>	20m
<b>Width:</b>	1m
<b>Mass/Weight:</b>	1.4kg/m <sup>2</sup>
<b>Roll Weight:</b>	28kg
<b>Surface Finishes:</b>	(upper) Sanded (lower) Thermo-fusible Film
<b>Selvedge:</b>	None

### INSTALLATION

<b>Membrane Bond:</b>	Loose Laid
<b>Lap Bond:</b>	None

For further information please refer the 'IKO BUFR System Guidance Document'

### DISCLAIMER

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserve the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.