

IKOfix TOOTHED FLATBAR

PRODUCT INFORMATION

Used for securing the Armourplan or Spectraplan membrane at the perimeter of a mechanically fixed or ballasted IKO Polymeric roofing system. Should be installed at the roof perimeter, base of upstands and penetrations, and at all changes in direction using suitable IKOfix fasteners in accordance with IKO Polymeric technical guidelines.

Description	System Restraint
Material	Steel
Length	2250mm
Width	30mm
Thickness	1mm
Hole Diameter	5.0mm/17mm
Product Number	05495225


FEATURES & BENEFITS

- Cold Application
- Quick and easy installation
- Cost effective application





INSTALLATION

Position the Toothed Flatbar and secure using suitable IKOfix fasteners at maximum centres of 150mm or as per the IKO Polymeric wind uplift calculation. Allow a 10mm gap between lengths of Toothed Flatbar. Cover the bar ends with a sacrificial layer of membrane to protect the waterproofing from sharp edges.



TECHNICAL SPECIFICATION

Material	Steel
Length	2250mm
Gauge	1mm
Gauge Tolerance	±0.07mm
Length Tolerance	±3.0mm
General Tolerance	±0.4mm



STORAGE

IKOfix Toothed Flatbars should be kept dry. They should be stored raised off the surface of the roof and covered with a suitable waterproof layer.

FURTHER PRODUCT INFORMATION

Full product literature, health & safety and technical sheets are available as downloads from our website www.ikopolymeric.com or on request by email polymeric.marketing@iko.com.