

IKO ULTRA GOLD 20

PRODUCT INFORMATION

IKO Ultra Gold 20 is a fully bonded torch-applied, polyester reinforced, SBS modified bitumen capsheet with added fire retardant. It has an upper surface finish of mineral granules and a thermo-fusible film on the underside.



Colour	Product Code
Brown	60183823
Black	60183824
Green	60183827

USE

This product is for use as a capsheet layer within an IKO high performance built up roofing system specification.

The product must be applied by an IKO Approved Installer. All work must be undertaken in accordance with the requirements of the specific information provided with the issued IKO Specification document, or guidance documents where applicable.

INDEPENDENT ACCREDITATION



The product carries a Declaration of Performance Certificate, Agreement Certificate 91/2671, and is UK Conformity Assessed.

FEATURES & BENEFITS

High Performance – Exceptional dimensional stability and tensile strength.

Fire Performance – Incorporates Prevent Graphite Fire Wall Technology with self-extinguishing properties.

High Specification – Forms part of an IKO flat roofing specification offer.

COMPOSITION

Bitumen Modification:	SBS
Carrier:	Polyester
Form:	Roll
Colour:	Brown/ Black/ Green
Length:	8m
Width:	1m
Mass/Weight:	4.75kg/m ²
Roll Weight:	38kg
Surface Finishes:	(upper) Mineral (lower) Thermo-fusible film
Selvedge:	(upper) 75mm

INSTALLATION

Membrane Bond:	Torch applied
Lap Bond:	Torch applied

PERFORMANCE

For key product performance characteristics, please refer to the [IKO Declaration of Performance \(DoP\)](#)

DISCLAIMER

As this product is utilised within an Approved Contractor network and guided by an IKO Specification document, where omission or differing information exists the IKO Specification document will take precedence.

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserve the right to amend and/or withdraw this document without notice. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.