



SAFETY DATA SHEET
IKO Bonding Agent
Version 4

Date of Issue: 30/05/2022 Supersedes date: 05/11/2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name IKO Bonding Agent
Product number 023500005 AO3927 UFI Code: 087F-9Q4D-M52V-0X60

1.2. Relevant identified uses of the substance or mixture and uses advised against Identified uses

Adhesive.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier IKO PLC
Head Office
Appley Lane North
Appley Bridge
Wigan
Lancashire
WN6 9AB
England

1.4. Emergency telephone number

Emergency telephone +44 01827 69662 (NOT 24HRS - 8am-5pm mon-fri)

National emergency telephone number National Poisons Information Service (UK) TEL: 0844 892 0111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225
Health hazards Skin Irrit. 2 - H315 STOT SE 3 - H336
Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Human health The liquid may be irritating to skin.

Environmental The product contains a substance which is harmful to aquatic organisms.

Physicochemical The product is highly flammable. Vapours may form explosive mixtures with air.

2.2. Label elements



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

Hazard pictograms



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

EU limit value for this product (cat A/h): 750g/l (2010). This product contains max 550 g/l VOC.

Contains

CYCLOHEXANE, hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane, ETHYL ACETATE

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

CYCLOHEXANE		30-60%
CAS number: 110-82-7	EC number: 203-806-2	REACH registration number: 01-2119463273-41-0000
M factor (Acute) = 1	M factor (Chronic) = 1	
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H312 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane			10-30%
CAS number: —	EC number: 921-024-6	REACH registration number: 01-2119475514-35-0001	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
ETHYL ACETATE			1-5%
CAS number: 141-78-6	EC number: 205-500-4	REACH registration number: 01-2119475103-46-0017	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			
HEXANE-norm			<1%
CAS number: 110-54-3	EC number: 203-777-6	REACH registration number: 01-2119480412-44-0009	
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361f STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
POLYAMINE AMIDE SALT			<1%
CAS number: —	EC number: 935-868-8		
Classification Skin Irrit. 2 - H315			



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

XYLENE			<1%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0030	

Classification
Flam. Liq. 3 - H226
Acute Tox. 4 - H312
Acute Tox. 4 - H332
Skin Irrit. 2 - H315
Eye Irrit. 2 - H319
STOT SE 3 - H335
STOT RE 2 - H373
Asp. Tox. 1 - H304

ETHYLBENZENE			<1%
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-0018	

Classification
Flam. Liq. 2 - H225
Acute Tox. 4 - H332
STOT RE 2 - H373
Asp. Tox. 1 - H304

ISO-BUTANOL			<1%
CAS number: 78-83-1	EC number: 201-148-0	REACH registration number: 01-2119484609-23-0003	

Classification
Flam. Liq. 3 - H226
Skin Irrit. 2 - H315
Eye Dam. 1 - H318
STOT SE 3 - H335, H336

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Ingestion	Rinse mouth thoroughly with water. Get medical attention.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---



IKO Bonding Agent

Version 4

Date of Issue: 30/05/2022

Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	May cause discomfort if swallowed. May cause stomach pain or vomiting.
Skin contact	Prolonged skin contact may cause redness and irritation.
Eye contact	May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use fire-extinguishing media suitable for the surrounding fire. Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Heating may generate flammable vapours. The product is highly flammable.

Hazardous combustion products Does not decompose when used and stored as recommended.

5.3. Advice for firefighters

Protective actions during firefighting Control run-off water by containing and keeping it out of sewers and watercourses. Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes.

Special protective equipment for firefighters Wear chemical protective suit.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Keep away from heat, sparks and open flame. Keep container tightly closed. Keep only in the original container.
Storage class	Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

CYCLOHEXANE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 350 mg/m³

Short-term exposure limit (15-minute): WEL 300 ppm 1050 mg/m³

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

HEXANE-norm

Long-term exposure limit (8-hour TWA): WEL 20 ppm 72 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m³

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m³

Sk

ISO-BUTANOL

Long-term exposure limit (8-hour TWA): WEL 50 ppm 154 mg/m³

Short-term exposure limit (15-minute): WEL 75 ppm 231 mg/m³

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

Ingredient comments	WEL = Workplace Exposure Limits
----------------------------	---------------------------------

CYCLOHEXANE (CAS: 110-82-7)

DNEL

Consumer - Oral; Long term systemic effects: 59.4 mg/kg bw/day
Consumer - Dermal; Long term systemic effects: 1186 mg/kg bw/day
Workers - Dermal; Long term systemic effects: 2016 mg/kg bw/day
Consumer - Inhalation; Short term local effects: 412 mg/m³
Consumer - Inhalation; Short term systemic effects: 412 mg/m³
Workers - Inhalation; Short term local effects: 700 mg/m³
Workers - Inhalation; Short term systemic effects: 700 mg/m³
Consumer - Inhalation; Long term local effects: 206 mg/m³
Workers - Inhalation; Long term local effects: 700 mg/m³
Consumer - Inhalation; Long term systemic effects: 206 mg/m³
Workers - Inhalation; Long term systemic effects: 700 mg/m³



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

- PNEC**
- Fresh water; 0.207 mg/l
 - Sediment (Freshwater); 3.627 mg/kg
 - STP; 3.24 mg/l
 - Soil; 2.99 mg/kg

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Ingredient comments WEL = Workplace Exposure Limits

- DNEL**
- Consumer - Oral; Long term systemic effects: 699 mg/kg bw/day
 - Consumer - Dermal; Long term systemic effects: 699 mg/kg bw/day
 - Workers - Dermal; Long term systemic effects: 773 mg/kg bw/day
 - Consumer - Inhalation; Long term systemic effects: 608 mg/m³

ETHYL ACETATE (CAS: 141-78-6)

- DNEL**
- Workers - Inhalation; Short term systemic effects: 1468 mg/m³
 - Workers - Inhalation; Short term local effects: 1468 mg/m³
 - Consumer - Inhalation; Short term systemic effects: 734 mg/m³
 - Consumer - Inhalation; Short term local effects: 374 mg/m³
 - Workers - Inhalation; Long term local effects: 734 mg/m³
 - Workers - Dermal; Long term systemic effects: 63 mg/kg bw/day
 - Workers - Inhalation; Long term systemic effects: 734 mg/m³
 - Consumer - Dermal; Long term systemic effects: 37 mg/kg bw/day
 - Consumer - Inhalation; Long term systemic effects: 367 mg/m³
 - Consumer - Oral; Long term systemic effects: 4.5 mg/kg bw/day
 - Consumer - Inhalation; Long term local effects: 367 mg/m³

- PNEC**
- Fresh water; 0.26 mg/l
 - marine water; 0.026 mg/l
 - Intermittent release; 1.65 mg/l
 - Sediment (Freshwater); 1.25 mg/kg
 - Sediment (Marinewater); 0.125 mg/kg
 - Soil; 0.24 mg/kg
 - STP; 650 mg/l

ISO-BUTANOL (CAS: 78-83-1)

- DNEL**
- Workers - Inhalation; Long term local effects: 310 mg/m³
 - Consumer - Oral; Long term systemic effects: 25 mg/kg
 - Consumer - Inhalation; Long term local effects: 55 mg/m³

- PNEC**
- Fresh water; 0.4 mg/l
 - marine water; 0.04 mg/l
 - Sediment (Freshwater); 1.52 mg/kg
 - Sediment (Marinewater); 0.152 mg/kg
 - Soil; 0.0699 mg/kg
 - STP; 10 mg/l
 - Intermittent release; 11 mg/l

8.2. Exposure controls

Protective equipment





IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

Appropriate engineering controls	Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	The following protection should be worn: Chemical splash goggles.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Nitrile rubber. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear apron or protective clothing in case of contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Wash contaminated clothing before reuse. Wash hands after handling. Eating, smoking and water fountains prohibited in immediate work area.
Respiratory protection	In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Wear a respirator fitted with the following cartridge: ABEK2-P3 Particulate filter, type P3.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Various colours.
Odour	aromatic hydrocarbons
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	Estimated value. 62-100°C @
Flash point	Estimated value. -35°C
Evaporation rate	Not determined.
Evaporation factor	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Estimated value. : 0.6% - 13%
Other flammability	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0.80 @ 20°C
Bulk density	Not available.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not available.



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

Auto-ignition temperature	230°C
Decomposition Temperature	Not available.
Viscosity	Kinematic viscosity > 20.5 mm ² /s.
Explosive properties	Not available.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not available.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Other information	No information required.
Refractive index	Not available.
Particle size	Not available.
Molecular weight	Not available.
Volatility	Not available.
Saturation concentration	Not available.
Critical temperature	Not available.
Volatile organic compound	EU limit value for this product (cat A/h): 750g/l (2010). This product contains max 550 g/l VOC.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	No particular stability concerns. Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Not applicable. Not relevant.
---	-------------------------------

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Strong oxidising agents. Strong acids. Strong alkalis.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

ATE dermal (mg/kg) 4,878.05

Toxicological information on ingredients.

CYCLOHEXANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀
mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀
mg/kg) 2,000.0

Species Rabbit

ATE dermal (mg/kg) 2,000.0

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Toxicological effects No information available.

Acute toxicity - oral

Acute toxicity oral (LD₅₀
mg/kg) 5,840.0

Species Rat

Notes (oral LD₅₀) Not known. Data lacking.

ATE oral (mg/kg) 5,840.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀
mg/kg) 2,920.0

Species Rat

Notes (dermal LD₅₀) Data lacking.

ATE dermal (mg/kg) 2,920.0

Acute toxicity - inhalation

Acute toxicity inhalation
(LC₅₀ vapours mg/l) 25.2

Species Rat

ATE inhalation (vapours
mg/l) 25.2

Skin corrosion/irritation

Animal data Data lacking.

Serious eye damage/irritation



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

Serious eye damage/irritation	Data lacking.
<u>Aspiration hazard</u>	
Aspiration hazard	Kinematic viscosity > 20.5 mm ² /s.
Inhalation	May cause respiratory system irritation.
Ingestion	May cause stomach pain or vomiting.
Skin contact	Irritating to skin.
Eye contact	May cause severe eye irritation.
Acute and chronic health hazards	Vapour from this product may be hazardous by inhalation.
Route of exposure	Inhalation Skin absorption Ingestion. Skin and/or eye contact
Target organs	No specific target organs known.
Medical symptoms	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Headache. Fatigue. Nausea, vomiting.
Medical considerations	No information available.

ETHYL ACETATE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,620.0

Species Rat

ATE oral (mg/kg) 5,620.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 20,000.0

Species Rabbit

ATE dermal (mg/kg) 20,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 30.0

Species Rat

ATE inhalation (vapours mg/l) 30.0

HEXANE-norm

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 25,000.0



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

Species	Rat
ATE oral (mg/kg)	25,000.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC ₅₀ gases ppmV)	48,000.0
Species	Rat
ATE inhalation (gases ppm)	48,000.0

XYLENE

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD ₅₀ mg/kg)	4,000.0
Species	Rat
ATE oral (mg/kg)	4,000.0
<u>Acute toxicity - dermal</u>	
ATE dermal (mg/kg)	1,100.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC ₅₀ gases ppmV)	6,700.0
Species	Rat
ATE inhalation (gases ppm)	6,700.0
<u>Carcinogenicity</u>	
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.

ETHYLBENZENE

<u>Acute toxicity - inhalation</u>	
ATE inhalation (gases ppm)	4,500.0
ATE inhalation (vapours mg/l)	11.0
ATE inhalation (dusts/mists mg/l)	1.5
<u>Carcinogenicity</u>	
IARC carcinogenicity	IARC Group 2B Possibly carcinogenic to humans.

ISO-BUTANOL

<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD ₅₀ mg/kg)	6,400.0



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

Species	Rat
ATE oral (mg/kg)	6,400.0
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD ₅₀ mg/kg)	4,240.0
Species	Rabbit

SECTION 12: Ecological information

Ecological information on ingredients.

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Ecotoxicity	Dangerous for the environment.
-------------	--------------------------------

12.1. Toxicity

Ecological information on ingredients.

CYCLOHEXANE

Acute aquatic toxicity

LE(C) ₅₀	0.1 < L(E)C ₅₀ ≤ 1
M factor (Acute)	1
Acute toxicity - fish	LC ₀ , 96 hours: 4.53 mg/l, Pimephales promelas (Fat-head Minnow)
Acute toxicity - aquatic invertebrates	EC ₀ , 48 hours: 0.9 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₀ , 72 hours: 3.4 mg/l, Algae
Acute toxicity - microorganisms	EC ₅₀ , 20 hours: 29 mg/l, Bacteria

Chronic aquatic toxicity

M factor (Chronic)	1
--------------------	---

hydrocarbons, C6-C7,n-alkanes, isoalkanes, cyclics, <5% n-hexane

Acute aquatic toxicity

Acute toxicity - fish	LC ₀ , hours: >1-<10 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 3 mg/l, Daphnia magna
Acute toxicity - aquatic plants	LC ₀ , hours: >1-<10 mg/l, Algae

ETHYL ACETATE

Acute aquatic toxicity

Acute toxicity - fish	EC ₅₀ , 48 hours: 610 mg/l, Marinewater fish LC ₅₀ , 96 hours: 230 mg/l, Pimephales promelas (Fat-head Minnow)
-----------------------	---



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 11.5 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 48 hours: 5600 mg/l, Freshwater algae

HEXANE-norm

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, EC₅₀, IC₅₀ : 10 mg/l, Fish

Acute toxicity - aquatic invertebrates LC₅₀, EC₅₀, IC₅₀ : 10 mg/l, Daphnia magna

Acute toxicity - aquatic plants LC₅₀, EC₅₀, IC₅₀ : 10 mg/l, Algae

XYLENE

Acute aquatic toxicity

Acute toxicity - fish , 48 hours: > 1-10 mg/l, Freshwater fish

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 11.5 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 72 hours: 100 mg/l, Algae

ISO-BUTANOL

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 1.220 mg/l, Pimephales promelas (Fat-head Minnow)

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Partition coefficient Not available.

Ecological information on ingredients.

CYCLOHEXANE

Bioaccumulative potential BCF: 167,

ETHYL ACETATE

Bioaccumulative potential BCF: 30,

Partition coefficient Not available.

XYLENE

Bioaccumulative potential The product does not contain any substances expected to be bioaccumulating.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

Ecological information on ingredients.

ETHYL ACETATE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

XYLENE

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

ETHYL ACETATE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

XYLENE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

ETHYL ACETATE

Other adverse effects Not known.

XYLENE

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1133

UN No. (IMDG) 1133

UN No. (ICAO) 1133

UN No. (ADN) 1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ADHESIVES

Proper shipping name (IMDG) ADHESIVES

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (ADN) ADHESIVES

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

ADN packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-D

ADR transport category 2

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

National regulations	Health and Safety at Work etc. Act 1974 (as amended). The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended). The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Commission Directive 91/322/EEC of 29 May 1991 on establishing indicative limit values by implementing Council Directive 80/1107/EEC on the protection of workers from the risks related to exposure to chemical, physical and biological agents at work. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Authorisations (Annex XIV Regulation 1907/2006)	This product is/contains a substance that is included in REGULATION (EC) No 1907/2006 (REACH) ANNEX XVII - RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES. Entry number: 57

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments	updated VOC information
Issued by	OHS&E Department
Revision date	30/05/2022
Revision	3
Supersedes date	05/11/2019
Hazard statements in full	H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.
Store Between	Store Between 5'c - 25'c
Contains SVHC	NO

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.



IKO Bonding Agent
Version 4
Date of Issue: 30/05/2022

Version History

V1	March 2018	New Document
V2	June 2019	Added UFI Code, Updated Logo
V3	Nov. 2019	Amended Precautionary Statments in sect 2
V4	May 2022	Reviewed, amended data, updated voc information