

SAFETY DATA SHEET

30340350 - Spectraplan Contact Adhesive V1057

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product Code : 30340350
Type of product : Contact adhesive
UFI Code : 2CJJ-4EPX-AT2H-Y29K

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Main use category : Industrial uses, Professional use
Industrial/Professional use spec : Contact adhesive

1.2.2. Uses advised against

Restrictions on use : Not to be used for any purpose other than the one the product was designed for

1.3. Details of the supplier of the safety data sheet**Manufacturer / Supplier**

IKO PLC
Appley Lane North
Appley Bridge
Wigan
WN6 9AB

1.4. Emergency telephone number

Emergency number : Tel.: 00 32 (0)70 245 245 (Anti-gifcentrum België/Centre Anti-Poison Belgique)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Harmful by prolonged exposure. Dangerous for the environment.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

GHS07

GHS09

Signal word (CLP) :

: Danger

Hazard statements (CLP) :

: H225 - Highly flammable liquid and vapour.
H315 - Causes skin irritation.
H336 - May cause drowsiness or dizziness.
H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) :

: P210 - Keep away from sources of ignition - No smoking.
P241 - Use explosion-proof electrical, ventilating, lighting equipment.
P271 - Use only outdoors or in a well-ventilated area.
P312 - Call a doctor if you feel unwell.
P370+P378 - In case of fire, use: dry chemical powder, alcohol-resistant foam, carbon dioxide (CO2), water spray, sand, earth to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

EUH-statements :

: EUH066 - Repeated exposure may cause skin dryness or cracking.

Extra phrases :

: Contains : Cyclohexane, aliphatic hydrocarbons, Acetone.

2.3. Other hazards

Other hazards not contributing to the classification : Vapour mixes readily with air, forming explosive mixtures.



SAFETY DATA SHEET

30340350 - Spectraplan Contact Adhesive V1057

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Cyclohexane	(CAS-No.) 110-82-7 (EC-No.) 203-806-2 (EC Index-No.) 601-017-00-1 (REACH-no) 01-2119463273-41	20 - 30	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	(EC-No.) 927-510-4 (EC Index-No.) 927-510-4	10 - 30	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
acetone; propan-2-one; propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8	10 - 20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Hydrocarbons, C6 isoalkanes, <5% n-hexane	(EC-No.) 931-254-9 (REACH-no) 01-2119484651-34	5 - 15	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. Take victim to a doctor if irritation persists.
First-aid measures after inhalation	: Remove victim to fresh air. If not breathing, give artificial respiration. When there is no quick recovery : consult a doctor/medical service.
First-aid measures after skin contact	: Rinse with water. Wash with water and soap. Take victim to a doctor if irritation persists. Repeated or prolonged skin contact may cause dermatitis and defatting.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Take victim to an ophthalmologist if irritation persists.
First-aid measures after ingestion	: In all cases of doubt, or when symptoms persist, seek medical attention. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Dizziness. Nausea. Dry skin. Headache. Unconsciousness. skin irritation.
Symptoms/effects after skin contact	: Harmful when absorbed into the body through the skin. ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: May produce an allergic reaction. Irritating to skin. May cause skin irritation / dermatitis.
Symptoms/effects after eye contact	: Irritating to eyes. Pain. Redness of the eye tissue.

4.3. Indication of any immediate medical attention and special treatment needed

Contains: petrol. Causes damage to the central nervous system.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Dry powder. Carbon dioxide. Water haze. Carbon dioxide. Powder. Foam. Sand. sand/earth.
Unsuitable extinguishing media	: Do not use a high volume water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: May form flammable en explosive vapour-air mixture. Possible ignition from a distance. Will float and can be reignited on water surface.
Explosion hazard	: Atex klasse IIA, T3.

5.3. Advice for firefighters

Precautionary measures fire	: Evacuate unnecessary personnel.
Firefighting instructions	: Eliminate all ignition sources if safe to do so. Use water spray or fog for cooling exposed containers. Prevent fire fighting water from entering the environment. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.



SAFETY DATA SHEET

30340350 - Spectraplan Contact Adhesive V1057

Other information : Use water spray or fog for cooling exposed containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate air ventilation. When handling product, avoid contact with skin and eyes. No naked flames or sparks. In order to rule out potential electrostatic discharge production, the system must be adequately grounded. Do not inhale vapour. Stop engines and no smoking. Shut off leaks if without risks.

6.1.1. For non-emergency personnel

Protective equipment : Use protective clothing. See Heading 8.
 Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable protective clothing and gloves. Wear a self contained breathing apparatus.
 Emergency procedures : Ventilate area. Stop leak if safe to do so. Stop release.

6.2. Environmental precautions

Substance must not be discharged into the sewer.

6.3. Methods and material for containment and cleaning up

For containment : Shut off leaks if without risks. Contain released substance, pump into suitable containers. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal.
 Methods for cleaning up : Wash down leftovers with plenty of water.
 Other information : May form flammable vapour-air mixture.

6.4. Reference to other sections

Exposure controls and personal protection. See Heading 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : if necessary: Ventilation, local exhaust, or breathing protection. In use, may form flammable vapour-air mixture. Handle empty containers with care because residual vapours are flammable. ventilate the area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Precautions for safe handling : Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not get in eyes, on skin, or on clothing. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. No naked flames, sparks, and do not smoke. Do not handle until all safety precautions have been read and understood. Keep away from ignition sources (including static discharges). Provide good ventilation in process area to prevent formation of vapour. Take precautionary measures against static discharge.
 Handling temperature : 15 - 25 °C
 Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use explosion-proof electrical/ventilating/lighting equipment. Provide adequate ventilation.
 Storage conditions : Store in original container. Keep container tightly closed.
 Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.
 Maximum storage period : 12 months
 Storage temperature : 10 - 20 °C
 Storage area : Keep container tightly closed in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Fireproof storeroom. Keep only in the original container.
 Special rules on packaging : meet the legal requirements.

7.3. Specific end use(s)

Contact adhesive.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Cyclohexane (110-82-7)		
EU	IOELV TWA (mg/m ³)	700 mg/m ³
EU	IOELV TWA (ppm)	200 ppm
Belgium	Limit value (mg/m ³)	350 mg/m ³
Belgium	Limit value (ppm)	100 ppm
Germany	TRGS 910 Acceptable concentration notes	



SAFETY DATA SHEET

30340350 - Spectraplan Contact Adhesive V1057

acetone; propan-2-one; propanone (67-64-1)

Belgium	Limit value (mg/m ³)	1210 mg/m ³ 2009
Belgium	Limit value (ppm)	500 ppm 2009
Belgium	Short time value (mg/m ³)	2420 mg/m ³ 2009
Belgium	Short time value (ppm)	1000 ppm 2009
Germany	TRGS 910 Acceptable concentration notes	

8.2. Exposure controls

Appropriate engineering controls:

Ensure adequate ventilation. Wear suitable respiratory equipment in case of insufficient ventilation.

Personal protective equipment:

In case of splash hazard: safety glasses. Gloves.

Materials for protective clothing:

synthetic material. latex. polyethylene/ethylevinylalcohol. PVC. synthetic rubber

Hand protection:

Chemical resistant gloves (according to European standard EN 374 or equivalent)

Eye protection:

Safety glasses

Skin and body protection:

Standard working clothes

Respiratory protection:

Ensure adequate ventilation. If local exhaustion is insufficient, wear full-face mask.

Personal protective equipment symbol(s):



Environmental exposure controls:

See section 6,7, 12 en 13.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Yellow. Brown-yellow.
Odour	: Aromatic odour.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 55 °C
Flash point	: -26 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 160 hPa 20°C
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.81 g/cm ³ ± 0.05
Solubility	: Water: insoluble in water
Log Pow	: No data available



SAFETY DATA SHEET

30340350 - Spectraplan Contact Adhesive V1057

Viscosity, kinematic	: No data available
Viscosity, dynamic	: 250 - 350 mPa·s (20°C Spindel 4 20RPM)
Explosive properties	: Product is not explosive but may form flammable/explosive vapour-air mixture. Explosion Class: IIa, T3.
Oxidising properties	: No data available
Explosive limits	: 1.1 - 7.4 vol %

9.2. Other information

Other properties : Contains volatile component(s).

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Vapours may form flammable and explosive mixture with air.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

fire, naked flames. sparks. Heat. direct sunlight.

10.5. Incompatible materials

When liquid avoid. Water. Certain plastic materials.

10.6. Hazardous decomposition products

Hazardous smoke may be released during heating until decomposition.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Cyclohexane (110-82-7)

LD50 oral rat	> 5000 kilogram
LD50 dermal rat	> 2000 mg/kg

acetone; propan-2-one; propanone (67-64-1)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 15000 mg/kg
LC50 inhalation rat (mg/l)	76 mg/l/4h

Skin corrosion/irritation	: Irritant to the skin. in case of longer skin contact irritation can appear, i.g.degrease
Serious eye damage/irritation	: Eye irritation
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Floats on water, evaporates quickly, danger of pollution of drinking water when large quantities of the product enters the soil. . Avoid undiluted product to come into sewer or superficial water.
Ecology - water	: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
Acute aquatic toxicity	: Very toxic to aquatic life.
Chronic aquatic toxicity	: Very toxic to aquatic life with long lasting effects.

Cyclohexane (110-82-7)

LC50 fish 1	4.53 mg/l (Pimephales promelas)
-------------	---------------------------------



SAFETY DATA SHEET

30340350 - Spectraplan Contact Adhesive V1057

EC50 Daphnia 1	0.9 mg/l 48h
EC50 other aquatic organisms 1	3.4 mg/l 72h (Selenastrum capricornutum)

acetone; propan-2-one; propanone (67-64-1)

LC50 fish 1	> 5000 mg/l 96u
EC50 Daphnia 1	> 10000 mg/l 48u

12.2. Persistence and degradability

Cyclohexane (110-82-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

acetone; propan-2-one; propanone (67-64-1)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

12.3. Bioaccumulative potential

Cyclohexane (110-82-7)

Log Pow	3.4
Bioaccumulative potential	None reasonably foreseeable.

acetone; propan-2-one; propanone (67-64-1)

Log Pow	-0.24
Bioaccumulative potential	There is no bioaccumulation.

12.4. Mobility in soil

Cyclohexane (110-82-7)

Ecology - soil	Insoluble in water.
----------------	---------------------

12.5. Results of PBT and vPvB assessment

Component

Cyclohexane (110-82-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
acetone; propan-2-one; propanone (67-64-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Additional information : Handle uncleaned empty containers as highly flammable and dangerous.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: UN 1133
UN-No. (IMDG)	: UN 1133
UN-No. (IATA)	: UN 1133
UN-No. (ADN)	: UN 1133
UN-No. (RID)	: UN 1133

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: ADHESIVES, containing a flammable liquid
Proper Shipping Name (IMDG)	: ADHESIVES, containing a flammable liquid
Proper Shipping Name (IATA)	: ADHESIVES, containing a flammable liquid
Proper Shipping Name (ADN)	: ADHESIVES, containing a flammable liquid
Proper Shipping Name (RID)	: ADHESIVES, containing a flammable liquid

SAFETY DATA SHEET

30340350 - Spectraplan Contact Adhesive V1057

Transport document description (ADR)	: UN 1133 ADHESIVES, containing a flammable liquid, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS
Transport document description (IMDG)	: UN 1133 , 3, II, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA)	: UN 1133 , 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN)	: UN 1133 , 3, II, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID)	: UN 1133 , 3, II, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3 (N)
Danger labels (ADR)	: 3, N



IMDG

Transport hazard class(es) (IMDG)	: 3 (N)
Danger labels (IMDG)	: 3, N



IATA

Transport hazard class(es) (IATA)	: 3 (N)
Hazard labels (IATA)	: 3, N



ADN

Transport hazard class(es) (ADN)	: 3
Danger labels (ADN)	: 3



RID

Transport hazard class(es) (RID)	: 3 (N)
Danger labels (RID)	: 3, N



14.4. Packing group

Packing group (ADR)	: II
Packing group (IMDG)	: II
Packing group (IATA)	: II
Packing group (ADN)	: II
Packing group (RID)	: II

14.5. Environmental hazards

Dangerous for the environment	: Yes
Marine pollutant	: Yes



SAFETY DATA SHEET

30340350 - Spectraplan Contact Adhesive V1057

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 640C
Vehicle for tank carriage : FL
Transport category (ADR) : 2
Tunnel restriction code (ADR) : D/E

Transport by sea

Transport regulations (IMDG) : Subject
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-D

Air transport

No data available

Inland waterway transport

No data available

Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Data sources : The information supplied has been based upon the current level of information available, for the purpose of specifying the requirements regarding environment, health and safety in conjunction with the product. They are not to be interpreted as a warranty.

Other information : This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.



SAFETY DATA SHEET
30340350 - Spectraplan Contact Adhesive V1057

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Version History.

V1	June 2015	New release for Classification, Labelling Packaging Regulations
V2	June 2015	Added UFI Code, amended logo