



IKO ARMOURPLAN PVC CONTACT ADHESIVE (20LTR)

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: IKO ARMOURPLAN PVC CONTACT ADHESIVE (20LTR)

Product Code: 44335320

Product UFI: 8YKU-CRRX-F34M-EPRV

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Adhesive.

1.3. Details of the supplier of the safety data sheet

Company name: IKO PLC

Appley Lane North

Appley Bridge

Wigan

Lancashire

WN6 9AB

UK

Tel: +44 1257 256864

Web: www.ikogroup.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1257 256864 Opening Times: 0900 - 1700 Monday to Friday

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Classification under CLP: This product has no classification under CLP.

Precautionary phrases: Very high VOC content 50% or above

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.



Safety Data Sheet
According to EC Regulation 1907/2006
(REACH) & 1272/2008 (CLP) & 453/2010/
Version 3

Revision: 20/06/2019

IKO ARMOURPLAN PVC CONTACT ADHESIVE (20LTR)

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ACETONE

EINECS	CAS	CLP Classification	Percent
200-662-2	67-64-1	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	10-30%

ETHYL METHYL KETONE - REACH registered number(s): 01-2119457290-43

201-159-0	78-93-3	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	30-50%
-----------	---------	-----------------------------------------------------------------------	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove from skin with paper or towel. Wash effected area thoroughly with soap and water. Seek medical advice if symptoms persist.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.



Safety Data Sheet
According to EC Regulation 1907/2006
(REACH) & 1272/2008 (CLP) & 453/2010/
Version 3

Revision: 20/06/2019

IKO ARMOURPLAN PVC CONTACT ADHESIVE (20LTR)

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.



IKO ARMOURPLAN PVC CONTACT ADHESIVE (20LTR)

Do not handle in a confined space. Avoid the formation or spread of mists in the air.
Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area.
Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ACETONE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1210 mg/m ³	3620 mg/m ³	-	-

ETHYL METHYL KETONE

UK	600 mg/m ³	899 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: If exposure levels are likely to be exceeded, use a full face mask fitted with an organic AXP3 filter for short term low level exposures. For long term or high level exposures, compressed airline breathing apparatus should be used.

Hand protection: Avoid skin contact. For repeated exposure use Viton or 4H chemical gloves. for low exposure use nitrile gloves. The user has a legal duty to carry out a COSHH risk assessment to determine the correct glove.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: No special requirement.

Section 9: Physical and chemical properties



IKO ARMOURPLAN PVC CONTACT ADHESIVE (20LTR)

9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Amber
Evaporation rate: Fast
Oxidising: Non-oxidising (by EC criteria)
Solubility in water: Insoluble
Viscosity: Viscous
Boiling point/range°C: 55-81
Flammability limits %: lower: 1.8
upper: 13
Flash point°C: -17
Autoflammability°C: 515
Relative density: 0.83

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ACETONE

IVN	RAT	LD50	5500	mg/kg
-----	-----	------	------	-------



Safety Data Sheet
According to EC Regulation 1907/2006
(REACH) & 1272/2008 (CLP) & 453/2010/
Version 3

Revision: 20/06/2019

IKO ARMOURPLAN PVC CONTACT ADHESIVE (20LTR)

ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable in part only.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Wet waste: Arrange for disposal by a licenced waste disposal company

Disposal of packaging: Arrange for disposal by a licenced waste disposal company

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.



Safety Data Sheet
According to EC Regulation 1907/2006
(REACH) & 1272/2008 (CLP) & 453/2010/
Version 3

Revision: 20/06/2019

IKO ARMOURPLAN PVC CONTACT ADHESIVE (20LTR)

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



Safety Data Sheet
According to EC Regulation 1907/2006
(REACH) & 1272/2008 (CLP) & 453/2010/
Version 3

Revision: 20/06/2019

IKO ARMOURPLAN PVC CONTACT ADHESIVE (20LTR)

Version History.

Version 1 June 2015	New release for Classification, Labelling Packaging Regulations
Version 2 April 2017	Revised to remove references to CHIP and R Phrases
Version 3 June 2019	Amended Logo, added UFI code

