

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
  - Trade name: ***IKOpro Quick Dry Bitumen Primer***
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

  - Application of the substance / the mixture *Bitumen Primer*
- **1.3 Details of the supplier of the safety data sheet**
  - **Manufacturer/Supplier:**

IKO PLC  
Appley Lane North  
Appley Bridge  
Wigan  
Lancashire  
WN6 9AB
  - **Further information obtainable from:**

UK: 01257 256779
- **1.4 Emergency telephone number:** +44 (0)1257 256864 Opening Times: 0900 - 1700 Monday to Friday




## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
  - **Classification according to Regulation (EC) No 1272/2008**

*Flam. Liq. 3 H226 Flammable liquid and vapour.*  
*Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.*  
*STOT SE 3 H336 May cause drowsiness or dizziness.*  
*Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.*
  - **Information concerning particular hazards for human and environment:**

*The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.*  
*At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.*
  - **Classification system:**

*The classification is according to the latest editions of the EU-lists, and extended by company and literature data.*
- **2.2 Label elements**
  - **Labelling according to Regulation (EC) No 1272/2008, 453/2010**

*The product is classified and labelled according to the CLP regulation.*
  - **Hazard pictograms**
    -   
    - GHS02   GHS07   GHS08
  - **Signal word** *Danger*
  - **Hazard-determining components of labelling:**

*Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromates*

(Contd. on page 2)

**Trade name: IKOpro Quick Dry Bitumen Primer**

(Contd. of page 1)

**Hazard statements**

- H226 Flammable liquid and vapour.
- H336 May cause drowsiness or dizziness.
- H304 May be fatal if swallowed and enters airways.
- H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

- EUH066 Repeated exposure may cause skin dryness or cracking.

**SECTION 3: Composition/information on ingredients**

**3.2 Chemical characterization: Mixtures**

- Description:** Mixture of aliphatic hydrocarbons and bitumen.

**Dangerous components:**

EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromates  <hr style="border-top: 1px dashed black;"/> Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412	50-75%
---	--	--------

- Additional information:** For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

**4.1 Description of first aid measures**

- After inhalation:** Supply fresh air; consult doctor in case of complaints.
- After skin contact:** Generally the product does not irritate the skin.
- After eye contact:** Rinse opened eye for several minutes under running water.
- After swallowing:** If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing agents:**

- CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 3)

Trade name: **IKOpro Quick Dry Bitumen Primer**

(Contd. of page 2)

- **5.2 Special hazards arising from the substance or mixture** Not applicable.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Wear fully protective suit.  
Wear self-contained respiratory protective device.

## **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Work only in fume cupboard.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

## **SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Protection of hands:** Solvent resistant gloves
- **Material of gloves**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Trade name: **IKOpro Quick Dry Bitumen Primer**

(Contd. of page 3)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **Appearance:**

· <b>Form:</b>	Fluid
· <b>Colour:</b>	Black
· <b>Odour:</b>	Petrol-like
· <b>pH-value:</b>	Not determined.

· **Change in condition**

· <b>Boiling point/Boiling range:</b>	145 °C
· <b>Flash point:</b>	24 °C
· <b>Ignition temperature:</b>	240 °C
· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· <b>Lower:</b>	0.5 Vol %
· <b>Upper:</b>	7.0 Vol %
· <b>Vapour pressure at 20 °C:</b>	5 hPa
· <b>Density at 20 °C:</b>	0.86 g/cm <sup>3</sup>
· <b>Solubility in / Miscibility with water:</b>	Insoluble.
· <b>organic solvents:</b>	Miscible with many organic solvents.
· <b>Viscosity:</b>	
· <b>Dynamic:</b>	Not determined.
· <b>Kinematic:</b>	9 - 14 mm <sup>2</sup> /s (40 °C)

· **Solvent content:**

· <b>VOC (EC)</b>	VOC limit value (cat A/h) 750 g/L 2010. Product contains 430 g/L.
-------------------	--

· **Solids content:** 46.0 %

· **9.2 Other information** No further information available.

**SECTION 10: Stability and reactivity**

· **10.2 Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid** No further relevant information available.

· **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 5)

Trade name: **IKOpro Quick Dry Bitumen Primer**

(Contd. of page 4)

· **10.6 Hazardous decomposition products:**

Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.

### SECTION 11: Toxicological information

· **11.1 Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromates**

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>5000 mg/kg (rabbit)
--------	------	----------------------

· **Primary irritant effect:**

· **on the skin:**

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

· **on the eye:** Splashes in the eyes may cause irritation and reversible local damage.

· **Sensitization:** No sensitizing effects known.

### SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclic, <2% aromates**

Inhalative	LC50	>4951 mg/l (rat)
------------	------	------------------

	EC50	>1000 mg/l (fish)
--	------	-------------------

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.


(Contd. on page 6)

Trade name: **IKOpro Quick Dry Bitumen Primer**

(Contd. of page 5)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- **14.1 UN-Number**  
· **ADR, IMDG** UN1268
- **14.2 UN proper shipping name**  
· **ADR** UN 1268, PETROLEUM PRODUCTS, N.O.S.  
· **IMDG** UN 1268, Petroleum products, n.o.s., 3, III, (24 °C c.c.)
- **14.3 Transport hazard class(es)**  
· **ADR, IMDG**  
  
· **Class** 3 Flammable liquids.  
· **Label** 3
- **14.4 Packing group**  
· **ADR, IMDG** III
- **14.5 Environmental hazards:**  
· **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Flammable liquids.  
· **Danger code (Kemler):** 30  
· **EMS Number:** F-E,S-E
- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**  
· **ADR**  
· **Limited quantities (LQ)** 5L  
· **Transport category** 3  
· **Tunnel restriction code** D/E
- **UN "Model Regulation":** UN1268, PETROLEUM PRODUCTS, N.O.S., 3, III

### SECTION 15: Regulatory information

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H226 Flammable liquid and vapour.

(Contd. on page 7)

**Trade name: IKOpro Quick Dry Bitumen Primer**

(Contd. of page 6)

*H304 May be fatal if swallowed and enters airways.*

*H336 May cause drowsiness or dizziness.*

*H412 Harmful to aquatic life with long lasting effects.*

**Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*GHS: Globally Harmonized System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

**Version History.**

Version 1.0 June 1st 2015 New release for Classification, Labelling Packaging Regulations