

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2020



Version number 1

Revision: 03.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- Trade name: **IKO Metatech Bitumen Primer**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 SU19 Building and construction work
- **Application of the substance / the mixture** Primer for liquid waterproofing of roofs.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 IKO Europe nv
 d'Herbouvillekaai 80
 B-2020 Antwerpen
 Belgium
 Tel.: +32 (0)3 248 30 00
 E-mail: sds.europe@iko.com
- **Further information obtainable from:**
 National Poisons Information Service UK: England and Wales: 0845 4647 Scotland: 08454 24 24 24; National Poisons Information Centre Ireland: +00 353 (0) 1 837 9964 or +00 353 (0) 1 809 2566. NPIS & NPIC services are provided exclusively for healthcare professionals working in NHS.
- **1.4 Emergency telephone number:**
 United Kingdom National Poisons Information Service (+44) 844 892 0111 - 0344 892 0111
 Ireland National Poisons Information Centre Tel: +353 1 8092566
 Emergency call only for healthcare professionals

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 Flam. Liq. 2 H225 Highly flammable liquid and vapour.
 Skin Irrit. 2 H315 Causes skin irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**


 GHS02 GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**
 methyl methacrylate
 Triethylene glycol dimethacrylate
 triisodecyl phosphite
- **Hazard statements**
 H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H335 May cause respiratory irritation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2020

Version number 1

Revision: 03.02.2020

Trade name: IKO Metatech Bitumen Primer

(Contd. of page 1)

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P262 Do not get in eyes, on skin, or on clothing.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Additional information:

- Can polymerize after significant exceeding of storagetime or storage temperature under heat development.
- Take precautionary measures against static discharge.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

- Description:** Solution of an acrylic polymer in acrylates and methacrylates.

Dangerous components:

CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥50-≤75%
CAS: 109-16-0 EINECS: 203-652-6 Reg.nr.: 01-2119969287-21	Triethylene glycol dimethacrylate Skin Sens. 1B, H317	≥1-≤10%
CAS: 38668-48-3 EINECS: 254-075-1	1,1'-(p-tolylimino)dipropan-2-ol Acute Tox. 2, H300 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	≥0.2-≤1%
CAS: 25448-25-3 Reg.nr.: 01-2119964066	triisodecyl phosphite Skin Sens. 1B, H317	≥0.1-<1%

- Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures
General information:

- Take affected persons out of danger area and lay down.
When in doubt or if symptoms are observed, seek medical advice.

- After inhalation:** Remove victim to fresh air. Seek medical attention if symptoms persist.

After skin contact:

- Immediately rinse with water.
If skin irritation continues, consult a doctor.

After eye contact:

- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

- After swallowing, rinse out mouth with plenty of water (only when conscious person) and seek medical attention immediately. Do not allow person to vomit. Let person rest.

4.2 Most important symptoms and effects, both acute and delayed

- Headache
Dizziness
Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

- No further relevant information available.

GB

(Contd. on page 3)

Trade name: IKO Metatech Bitumen Primer

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
Vapors are heavier than air and may form an explosive mixture with air.
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.
Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Keep away from heat and direct sunlight.
Use only in well ventilated areas.
Do not refill residue into storage receptacles.
Use the material only in places where open light, fire and other sources of ignition remain stay far away. Use personal protective equipment. (See chapter 8). If ventilation at the location is not possible or insufficient, extra measures need to be taken to guarantee a good ventilation of the workplace. The product can be electrostatically charged: Always use earth-lines when transferring from container to container. Avoid formation of flammable or explosive concentrations of vapors in the air and higher exposure levels than allowed. Observe the safety and health regulations at work.
- **Information about fire - and explosion protection:**
Fumes can combine with air to form an explosive mixture.
Use explosion-proof apparatus / fittings and spark-proof tools.
Highly volatile, flammable constituents are released during processing.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 4)

Trade name: IKO Metatech Bitumen Primer

(Contd. of page 3)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
Store in a cool location.
- **Information about storage in one common storage facility:**
Store away from oxidising agents.
Store away from foodstuffs.
- **Further information about storage conditions:**
Storage in a collecting room is required.
Store under lock and key and with access restricted to technical experts or their assistants only.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 80-62-6 methyl methacrylate

WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
-----	--

· DNELs

80-62-6 methyl metacrylate :

Inhalative DNEL (poulation) 74.3 mg/m³ (long term - systemic effects)

105 mg/m³ (long term - local effects)

DNEL (worker) 210 mg/m³ (long term - systemic effects)

210 mg/m³ (long term - local effects)

long term : 2.9 mg/m³/8h(aerosol- inhalation)

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

Suitable respiratory protective device recommended.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A

· Protection of hands:



Protective gloves

· Material of gloves

Butyl rubber, BR

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2020

Version number 1

Revision: 03.02.2020

Trade name: IKO Metatech Bitumen Primer

(Contd. of page 4)

- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact gloves made of the following materials are suitable:**
Butyl rubber, BR
- **Not suitable are gloves made of the following materials:** Leather gloves
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· Appearance:

Form: Fluid
Colour: Yellow tint

- **Odour:** Ester-like
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: Undetermined.
Initial boiling point and boiling range: 101 °C

- **Flash point:** 10 °C
- **Flammability (solid, gas):** Not applicable.
- **Ignition temperature:** 430 °C
- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 2.1 Vol %
Upper: 12.5 Vol %

- **Oxidising properties:** Not determined.

· **Vapour pressure at 20 °C:** 40 hPa

· **Density at 20 °C:** 1 g/cm³

· **Relative density:** Not determined.

· **Vapour density:** Not determined.

· **Evaporation rate:** Not determined.

· **Solubility in / Miscibility with water:** Insoluble.

· **Partition coefficient: n-octanol/water:** Not determined.

· Viscosity:

Dynamic at 20 °C: 100 mPas
Kinematic: Not determined.

· Solvent content:

VOC (EC) 0.0 g/l

- **9.2 Other information** No further information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2020

Version number 1

Revision: 03.02.2020

Trade name: IKO Metatech Bitumen Primer

(Contd. of page 5)

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with peroxides and other radical forming substances.
Exothermic reaction.
Exothermic polymerisation.
- **10.4 Conditions to avoid** Keep away from heat and direct sunlight.
- **10.5 Incompatible materials:**
Reacts with peroxides.
Reacts with reducing agents.
- **10.6 Hazardous decomposition products:** None at a proper use of the product.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**
methyl methacrylate:
LD50 oral (rat) : >5000 mg/kg
LC50 inhalation 4h(rat) : 29.8 mg/l
LD 50 dermal (rabbit) : >5000 mg/l

ATE (Acute Toxicity Estimates)		
Oral	LD50	>500-2,000 mg/kg

CAS: 80-62-6 methyl methacrylate		
Oral	LD50	7,872 mg/kg (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Irritant
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
80-62-6 methyl methacrylate
EC50/48h 69 mg/l (daphnia magna) (OECD 202)
EC50/72h >110 mg/l (Selenastrum capricornutum) (OECD201)
LC50/96h >79mg/l (Rainbow trout) (OECD 203)
- **12.2 Persistence and degradability** biodegradable
- **Other information:** The product is easily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** Groundwater can be contaminated.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2020

Version number 1

Revision: 03.02.2020

Trade name: IKO Metatech Bitumen Primer


(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal should be in accordance with applicable regional, national and local laws and regulations.
- **European waste catalogue** 080111
- **Uncleaned packaging:**
- **Recommendation:**
Packaging may be reused or recycled after cleaning.
Dispose of packaging according to regulations on the disposal of packagings.

SECTION 14: Transport information

- | | | |
|---|--|---------------------------|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | UN1866 | |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | UN1866 RESIN SOLUTION
UN 1866, Resin solution, 3, II, (10°C c.c.)
RESIN SOLUTION | |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA | <div style="text-align: center; margin-bottom: 10px;">  </div> <ul style="list-style-type: none"> · Class · Label | 3 Flammable liquids.
3 |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | II | |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | No | |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category | Warning: Flammable liquids.
33
F-E,S-D
B | |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. | |

(Contd. on page 8)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2020

Version number 1

Revision: 03.02.2020

Trade name: **IKO Metatech Bitumen Primer**

(Contd. of page 7)

- **Transport/Additional information:**

- **ADR**

- **Limited quantities (LQ)**

5L

- **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

- **Transport category**

2

- **Tunnel restriction code**

D/E

- **IMDG**

- **Limited quantities (LQ)**

5L

- **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

- **UN "Model Regulation":**

UN 1866 RESIN SOLUTION, 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed

- **Seveso category** P5c FLAMMABLE LIQUIDS

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **National regulations:**

- **Other regulations, limitations and prohibitive regulations**

- **Substances of very high concern (SVHC) according to REACH, Article 57**

This product does not contain any SVHC's.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet (SDS) is calculated with a Calculation method based on CLP Annex I, parts 2 to 5.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

H300 Fatal if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

- **Contact:** sds.europe@iko.com

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 9)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.02.2020

Version number 1

Revision: 03.02.2020

Trade name: IKO Metatech Bitumen Primer

(Contd. of page 8)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 2: Acute toxicity - oral – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB