

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.06.2020



Version number 1

Revision: 12.06.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: IKO Metatech Detail**
- **UFI: UERM-D8GQ-0009-HQ1Y**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 SU19 Building and construction work
- **Application of the substance / the mixture** Liquid waterproofing for roofdetails.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 IKO Europe nv
 d'Herbouvillekaai 80
 B-2020 Antwerpen
 Belgium
 Tel.: +32 (0)3 248 30 00
 E-mail: sds.europe@iko.com
- **Further information obtainable from:**
 National Poisons Information Service UK: England and Wales: 0845 4647 Scotland: 08454 24 24 24; National Poisons Information Centre Ireland: +00 353 (0) 1 837 9964 or +00 353 (0) 1 809 2566. NPIS & NPIC services are provided exclusively for healthcare professionals working in NHS.
- **1.4 Emergency telephone number:**
 United Kingdom National Poisons Information Service (+44) 844 892 0111 - 0344 892 0111
 Ireland National Poisons Information Centre Tel: +353 1 8092566
 Emergency call only for healthcare professionals

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 Flam. Liq. 2 H225 Highly flammable liquid and vapour.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2 H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H335 May cause respiratory irritation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**


 GHS02 GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**
 methyl methacrylate
 n-butyl acrylate
 2-ethylhexyl acrylate
 2-hydroxyethyl methacrylate
 tetramethylene dimethacrylate

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.06.2020

Version number 1

Revision: 12.06.2020

Trade name: IKO Metatech Detail

(Contd. of page 1)

Triethylene glycol dimethacrylate

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures
· Description: Solution of an acrylic polymer in acrylates and methacrylates.

· Dangerous components:

CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	25-40%
CAS: 103-11-7 EINECS: 203-080-7 Reg.nr.: 01-2119453158-37	2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335 Aquatic Chronic 3, H412	≥10-<25%
CAS: 141-32-2 EINECS: 205-480-7	n-butyl acrylate Flam. Liq. 3, H226 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	10-25%
CAS: 27813-02-1 EINECS: 248-666-3	methacrylic acid, monoester with propane-1,2-diol Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥5-<10%
CAS: 868-77-9 EINECS: 212-782-2	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	2.5-5%
CAS: 2082-81-7 EINECS: 218-218-1	tetramethylene dimethacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-5%
CAS: 109-16-0 EINECS: 203-652-6 Reg.nr.: 01-2119969287-21	Triethylene glycol dimethacrylate Skin Sens. 1B, H317	1-2.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures
· General information:

Take affected persons out of danger area and lay down.

Involve doctor immediately.

(Contd. on page 3)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.06.2020

Version number 1

Revision: 12.06.2020

Trade name: IKO Metatech Detail

(Contd. of page 2)

- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:**
If skin irritation continues, consult a doctor.
Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
Headache
Dizziness
Allergic reactions
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.
Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Keep away from heat and direct sunlight.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.06.2020

Version number 1

Revision: 12.06.2020

Trade name: IKO Metatech Detail

(Contd. of page 3)

Use only in well ventilated areas.

Do not refill residue into storage receptacles.

· **Information about fire - and explosion protection:**

Fumes can combine with air to form an explosive mixture.

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Store in a cool location.

· **Information about storage in one common storage facility:**

Store away from oxidising agents.

Store away from foodstuffs.

· **Further information about storage conditions:**

Storage in a collecting room is required.

Store under lock and key and with access restricted to technical experts or their assistants only.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

103-11-7 2-ethylhexyl acrylate

short term value : 38 mg/m³, 5 ppm

long term value : 38 mg/m³, 5 ppm

CAS: 80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm

Long-term value: 208 mg/m³, 50 ppm

CAS: 141-32-2 n-butyl acrylate

WEL Short-term value: 26 mg/m³, 5 ppm

Long-term value: 5 mg/m³, 1 ppm

· **DNELs**

80-62-6 methyl methacrylate :

Inhalative DNEL (poulation) 74.3 mg/m³ (long term - systemic effects)

105 mg/m³ (long term - local effects)

DNEL (worker) 210 mg/m³ (long term - systemic effects)

210 mg/m³ (long term - local effects)

103-11-7 2-ethylhexyl acrylate

Dermal DNEL 242µg/cm² (long term and short term)

Inhalative DNEL 37.5 mg/m³ (long term)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Suitable respiratory protective device recommended.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.06.2020

Version number 1

Revision: 12.06.2020

Trade name: IKO Metatech Detail

(Contd. of page 4)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• **Protection of hands:**



Protective gloves

• **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **For the permanent contact gloves made of the following materials are suitable:**

Butyl rubber, BR

• **Not suitable are gloves made of the following materials:** Leather gloves

• **Eye protection:**



Tightly sealed goggles

• **Body protection:** Use protective suit.

SECTION 9: Physical and chemical properties

• **9.1 Information on basic physical and chemical properties**

• **Appearance:**

Form:	Viscous
Colour:	Coloured
• Odour:	Ester-like
• Odour threshold:	Not determined.
• pH-value:	Not determined.

• **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 101 °C

• **Flash point:** 10 °C

• **Flammability (solid, gas):** Not applicable.

• **Ignition temperature:** Not determined.

• **Decomposition temperature:** Not determined.

• **Auto-ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

• **Explosion limits:**

Lower: 0.8 Vol %

Upper: 12.5 Vol %

• **Oxidising properties** Not determined.

• **Vapour pressure at 20 °C:** 47 hPa

• **Density at 20 °C:** 1.22 g/cm³

• **Relative density** Not determined.

• **Vapour density** Not determined.

• **Evaporation rate** Not determined.

(Contd. on page 6)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.06.2020

Version number 1

Revision: 12.06.2020

Trade name: **IKO Metatech Detail**

(Contd. of page 5)

- **Solubility in / Miscibility with water:** Insoluble.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
 - Dynamic at 20 °C:** 5,000 mPas
 - Kinematic:** Not determined.
- **Solvent content:**
 - VOC (EC)** 0.0 g/l
- **9.2 Other information** No further information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with peroxides and other radical forming substances.
Exothermic reaction.
Exothermic polymerisation.
- **10.4 Conditions to avoid** Keep away from heat and direct sunlight.
- **10.5 Incompatible materials:**
Reacts with peroxides.
Reacts with reducing agents.
- **10.6 Hazardous decomposition products:** None at a proper use of the product.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral	LD50	8,170 mg/kg (rat)
Dermal	LD50	18,155 mg/kg (rabbit)

CAS: 80-62-6 methyl methacrylate

Oral	LD50	7,872 mg/kg (rat)
------	------	-------------------

CAS: 103-11-7 2-ethylhexyl acrylate

Oral	LD50	5,660 mg/kg (rat)
Dermal	LD50	8,480 mg/kg (rabbit)

CAS: 141-32-2 n-butyl acrylate

Oral	LD50	900 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

CAS: 868-77-9 2-hydroxyethyl methacrylate

Oral	LD50	5,050 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Irritant
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.

(Contd. on page 7)

CB



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.06.2020

Version number 1

Revision: 12.06.2020

Trade name: IKO Metatech Detail

(Contd. of page 6)

- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
80-62-6 methyl methacrylate
EC50/48h 69 mg/l (daphnia magna) (OECD 202)
EC50/72h >110 mg/l (Selenastrum capricornutum) (OECD201)
LC50/96h >79mg/l (Rainbow trout) (OECD 203)
2-Ethylhexyl acrylate
EC50 48h(daphnia magna): 17.45 mg/l
LC50 48h (Leuciscus idus) : 23 mg/l
- **12.2 Persistence and degradability** Easily biodegradable
- **Other information:** The product is easily biodegradable.
- **12.3 Bioaccumulative potential** Potential to bioaccumulate.
- **12.4 Mobility in soil** Groundwater can be contaminated.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**
080111
080199
- **Uncleaned packaging:**
- **Recommendation:**
Packaging may be reused or recycled after cleaning.
Dispose of packaging according to regulations on the disposal of packagings.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.06.2020


Version number 1

Revision: 12.06.2020

Trade name: **IKO Metatech Detail**

(Contd. of page 7)

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA 	UN1263
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA 	UN1263 PAINT RELATED MATERIAL PAINT RELATED MATERIAL
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA 	<div style="text-align: center;">  </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids. 3
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	III
<ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): - · EMS Number: · Stowage Category 	Warning: Flammable liquids. - F-E,S-D A
<ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) 	Special provision 640D 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> · Transport category · Tunnel restriction code 	3 E
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 9)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.06.2020

Version number 1

Revision: 12.06.2020

Trade name: IKO Metatech Detail

(Contd. of page 8)

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**
This product does not contain any SVHC's.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheet (SDS) is calculated with a Calculation method based on CLP Annex I, parts 2 to 5.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H412 Harmful to aquatic life with long lasting effects.

· **Contact:** sds.europe@iko.com

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- SVHC: Substances of Very High Concern
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity - oral – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Skin Sens. 1B: Skin sensitisation – Category 1B
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**