

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.04.2020

Version number 1



Revision: 28.04.2020

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: IKO Metatech Finish**
- **UFI:** P1SM-X8AG-400S-434E
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**  
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites  
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
 SU19 Building and construction work
- **Application of the substance / the mixture** Acrylic sealant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
 IKO Europe nv  
 d'Herbouvillekaai 80  
 B-2020 Antwerpen  
 Belgium  
 Tel.: +32 (0)3 248 30 00  
 E-mail: sds.europe@iko.com
- **Further information obtainable from:**  
 National Poisons Information Service UK: England and Wales: 0845 4647 Scotland: 08454 24 24 24; National Poisons Information Centre Ireland: +00 353 (0) 1 837 9964 or +00 353 (0) 1 809 2566. NPIS & NPIC services are provided exclusively for healthcare professionals working in NHS.
- **1.4 Emergency telephone number:**  
 United Kingdom National Poisons Information Service (+44) 844 892 0111 - 0344 892 0111  
 Ireland National Poisons Information Centre Tel: +353 1 8092566  
 Emergency call only for healthcare professionals

## SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
 Flam. Liq. 2 H225 Highly flammable liquid and vapour.  
 Skin Irrit. 2 H315 Causes skin irritation.  
 Skin Sens. 1 H317 May cause an allergic skin reaction.  
 STOT SE 3 H335 May cause respiratory irritation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**  

GHS02 GHS07
- **Signal word** Danger
- **Hazard-determining components of labelling:**  
 methyl methacrylate  
 tetramethylene dimethacrylate
- **Hazard statements**  
 H225 Highly flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H335 May cause respiratory irritation.

(Contd. on page 2)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 28.04.2020

Version number 1

Revision: 28.04.2020

**Trade name: IKO Metatech Finish**

(Contd. of page 1)

**Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 Keep container tightly closed.
- P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
- P243 Take action to prevent static discharges.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves / eye protection / face protection.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### SECTION 3: Composition/information on ingredients

**3.2 Chemical characterisation: Mixtures**

- **Description:** Solution of an acrylic polymer in acrylates and methacrylates.

**Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥25-≤50%
CAS: 2082-81-7 EINECS: 218-218-1	tetramethylene dimethacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥0.5-<10%
CAS: 38668-48-3 EINECS: 254-075-1	1,1'-(p-tolylimino)dipropan-2-ol Acute Tox. 2, H300 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	≥0.1-≤0.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

**4.1 Description of first aid measures**
**General information:**

Take affected persons out of danger area and lay down.  
Involve doctor immediately.

**After inhalation:**

Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

If skin irritation continues, consult a doctor.  
Immediately wash with water and soap and rinse thoroughly.

**After eye contact:** Rinse opened eye for several minutes under running water.

**After swallowing:** If symptoms persist consult doctor.

**4.2 Most important symptoms and effects, both acute and delayed**

Headache  
Dizziness  
Allergic reactions

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### SECTION 5: Firefighting measures

**5.1 Extinguishing media**
**Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 28.04.2020

Version number 1

Revision: 28.04.2020

**Trade name: IKO Metatech Finish**

(Contd. of page 2)

- **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Carbon monoxide (CO)

Nitrogen oxides (NOx)

- **5.3 Advice for firefighters**

- **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

- **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Cool endangered receptacles with water spray.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Keep away from heat and direct sunlight.

Use only in well ventilated areas.

Do not refill residue into storage receptacles.

- **Information about fire - and explosion protection:**

Fumes can combine with air to form an explosive mixture.

Highly volatile, flammable constituents are released during processing.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store only in the original receptacle.

Store in a cool location.

- **Information about storage in one common storage facility:**

Store away from oxidising agents.

Store away from foodstuffs.

- **Further information about storage conditions:**

Storage in a collecting room is required.

Store under lock and key and with access restricted to technical experts or their assistants only.

Protect from frost.

Keep container tightly sealed.

(Contd. on page 4)

**Trade name: IKO Metatech Finish**

Store in cool, dry conditions in well sealed receptacles.

(Contd. of page 3)

## SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

103-11-7 2-ethylhexyl acrylate

short term value : 38 mg/m<sup>3</sup>, 5 ppm

long term value : 38 mg/m<sup>3</sup>, 5 ppm

### CAS: 80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m<sup>3</sup>, 100 ppm

Long-term value: 208 mg/m<sup>3</sup>, 50 ppm

- **DNELs**

80-62-6 methyl metacrylate :

Inhalative DNEL (poulation) 74.3 mg/m<sup>3</sup> (long term - systemic effects)

105 mg/m<sup>3</sup> (long term - local effects)

DNEL (worker) 210 mg/m<sup>3</sup> (long term - systemic effects)

210 mg/m<sup>3</sup> (long term - local effects)

103-11-7 2-ethylhexyl acrylate

Dermal DNEL 242µg/cm<sup>2</sup> (long term and short term)

Inhalative DNEL 37.5 mg/m<sup>3</sup> (long term)

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- **Respiratory protection:**

When ventilation is good, not needed. In case of brief exposure or low pollution use respiratory filter device (filter type A). In case of intensive or longer exposure use self-contained respiratory protective device.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

- **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **For the permanent contact gloves made of the following materials are suitable:**

Butyl rubber, BR

- **Not suitable are gloves made of the following materials:** Leather gloves

(Contd. on page 5)

# Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.04.2020

Version number 1

Revision: 28.04.2020

Trade name: **IKO Metatech Finish**

(Contd. of page 4)

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Use protective suit.

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**· **Appearance:**

**Form:** Viscous  
**Colour:** Different according to colouring

- **Odour:** Ester-like
- **Odour threshold:** Not determined.
- **pH-value:** Not determined.

· **Change in condition**

**Melting point/freezing point:** Undetermined.

**Initial boiling point and boiling range:** 101 °C

- **Flash point:** 10 °C
- **Flammability (solid, gas):** Not applicable.
- **Ignition temperature:** Not determined.
- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
  - Lower:** 2.1 Vol %
  - Upper:** 12.5 Vol %
- **Oxidising properties** Not determined.
- **Vapour pressure at 20 °C:** 47 hPa
- **Density at 20 °C:** 1.02 g/cm<sup>3</sup>
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with water:** Insoluble.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
  - Dynamic at 20 °C:** 5,000 mPas
  - Kinematic:** Not determined.
- **Solvent content:**
  - VOC (EC)** VOC limit value (cat A/i) 500 g/L 2010.  
Product contains 0 g/L.
- **9.2 Other information** No further information available.

## SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with peroxides and other radical forming substances.

(Contd. on page 6)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 28.04.2020

Version number 1

Revision: 28.04.2020

**Trade name: IKO Metatech Finish**

(Contd. of page 5)

- Exothermic reaction.
- Exothermic polymerisation.
- **10.4 Conditions to avoid** Keep away from heat and direct sunlight.
- **10.5 Incompatible materials:**
  - Reacts with peroxides.
  - Reacts with reducing agents.
- **10.6 Hazardous decomposition products:** None at a proper use of the product.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

#### ATE (Acute Toxicity Estimates)

Oral	LD50	>1,116-2,791 mg/kg
------	------	--------------------

#### CAS: 80-62-6 methyl methacrylate

Oral	LD50	7,872 mg/kg (rat)
------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
  - 80-62-6 methyl methacrylate
  - EC50/48h 69 mg/l (daphnia magna) (OECD 202)
  - EC50/72h >110 mg/l (Selenastrum capricornutum) (OECD201)
  - LC50/96h >79mg/l (Rainbow trout) (OECD 203)
  - 2-Ethylhexyl acrylate
  - EC50 48h(daphnia magna): 17.45 mg/l
  - LC50 48h (Leuciscus idus) : 23 mg/l
- **12.2 Persistence and degradability** Easily biodegradable
- **Other information:** The product is easily biodegradable.
- **12.3 Bioaccumulative potential** Potential to bioaccumulate.
- **12.4 Mobility in soil** Groundwater can be contaminated.
- **Additional ecological information:**
- **General notes:**
  - Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
  - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 7)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 28.04.2020

Version number 1

Revision: 28.04.2020

Trade name: **IKO Metatech Finish**


(Contd. of page 6)

- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **European waste catalogue**  
080111  
080199
- **Uncleaned packaging:**
- **Recommendation:**  
Packaging may be reused or recycled after cleaning.  
Dispose of packaging according to regulations on the disposal of packagings.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

### SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
- **ADR** UN 1263, Paint related material, 3, II, D/E
- **IMDG** UN 1263, Paint related material, 3, II, (10°C cc)
- **IATA** UN1263 PAINT RELATED MATERIAL
- **14.3 Transport hazard class(es)**
- **ADR, IMDG, IATA**
- 
- **Class** 3 Flammable liquids.
- **Label** 3
- **14.4 Packing group**
- **ADR, IMDG, IATA** II
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Hazard identification number (Kemler code):** 33
- **EMS Number:** F-E,S-D
- **Stowage Category** A
- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.
- **Transport/Additional information:**
- **ADR** Special provision 640D
- **Limited quantities (LQ)** 5L

(Contd. on page 8)



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 28.04.2020

Version number 1

Revision: 28.04.2020

**Trade name: IKO Metatech Finish**

(Contd. of page 7)

· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>Transport category</b>	2
· <b>Tunnel restriction code</b>	D/E
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1263 PAINT RELATED MATERIAL, 3, II

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed
- **Seveso category** P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**  
This product does not contain any SVHC's.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet (SDS) is calculated with a Calculation method based on CLP Annex I, parts 2 to 5.

- **Relevant phrases**  
H225 Highly flammable liquid and vapour.  
H300 Fatal if swallowed.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.
- **Contact:** sds.europe@iko.com
- **Abbreviations and acronyms:**  
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)  
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 9)





# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 28.04.2020

Version number 1

Revision: 28.04.2020

**Trade name: IKO Metatech Finish**

(Contd. of page 8)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 2: Acute toxicity - oral – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* **Data compared to the previous version altered.**

GB