

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2020


Version number 1

Revision: 18.12.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- Trade name: **IKO Metatech Mortar L**
- **UFI:** NSXP-7XAP-Q60D-KRXV
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 SU19 Building and construction work
- **Application of the substance / the mixture** Acrylic resin
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 IKO Europe nv
 d'Herbouvillekaai 80
 B-2020 Antwerpen
 Belgium
 Tel.: +32 (0)3 248 30 00
 E-mail: sds.europe@iko.com
- **Further information obtainable from:**
 National Poisons Information Service UK: England and Wales: 0845 4647 Scotland: 08454 24 24 24;
 National Poisons Information Centre Ireland: +00 353 (0) 1 837 9964 or +00 353 (0) 1 809 2566. NPIS
 & NPIC services are provided exclusively for healthcare professionals working in NHS.
- **1.4 Emergency telephone number:**
 United Kingdom National Poisons Information Service (+44) 844 892 0111 - 0344 892 0111
 Ireland National Poisons Information Centre Tel: +353 1 8092566
 Emergency call only for healthcare professionals

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 Flam. Liq. 2 H225 Highly flammable liquid and vapour.
 Skin Irrit. 2 H315 Causes skin irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 Carc. 2 H351 Suspected of causing cancer.
 STOT SE 3 H335 May cause respiratory irritation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**

 GHS02 GHS07 GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:**
 methyl methacrylate

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2020

Version number 1

Revision: 18.12.2020

Trade name: IKO Metatech Mortar L

(Contd. of page 1)

N,N-dimethyl-p-toluidine
n-butyl acrylate
tetramethylene dimethacrylate

- **Hazard statements**

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.

- **Precautionary statements**

P201 Obtain special instructions before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P262 Do not get in eyes, on skin, or on clothing.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

Can polymerize after significant exceeding of storagetime or storage temperature under heat development.
Take precautionary measures against static discharge.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** Solution of an acrylic polymer in acrylates and methacrylates.

- **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1 Reg.nr.: 01-2119452498-28	methyl methacrylate ----- Flam. Liq. 2, H225 Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥50-≤100%
CAS: 141-32-2 EINECS: 205-480-7	n-butyl acrylate ----- Flam. Liq. 3, H226 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	≥2.5-<10%
CAS: 99-97-8 EINECS: 202-805-4	N,N-dimethyl-p-toluidine ----- Acute Tox. 3, H301 Carc. 1B, H350 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	≥1-<2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.
When in doubt or if symptoms are observed, seek medical advice.

- **After inhalation:** Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2020

Version number 1

Revision: 18.12.2020

Trade name: IKO Metatech Mortar L

(Contd. of page 2)

- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
Headache
Dizziness
Allergic reactions
- **4.3 Indication of any immediate medical attention and special treatment needed**
Keep patient warm and quiet. Treat the symptoms.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Dry chemical, foam or carbon dioxide (CO₂).
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
Vapors are heavier than air and may form an explosive mixture with air.
Can form explosive gas-air mixtures.
In case of fire, the following can be released:
Carbon monoxide (CO)
Nitrogen oxides (NO_x)
- **5.3 Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
Mouth respiratory protective device.
- **Additional information**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Fumes can combine with air to form an explosive mixture.
Flammable liquid.
Cool endangered receptacles with water spray.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Keep away from ignition sources.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2020

Version number 1

Revision: 18.12.2020

Trade name: IKO Metatech Mortar L

(Contd. of page 3)

See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Keep away from heat and direct sunlight.
Use only in well ventilated areas.
Do not refill residue into storage receptacles.
Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Fumes can combine with air to form an explosive mixture.
Highly volatile, flammable constituents are released during processing.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
Store between 5°C and 25°C.
- **Information about storage in one common storage facility:**
Store away from oxidising agents.
Store away from foodstuffs.
- **Further information about storage conditions:**
Storage in a collecting room is required.
Store under lock and key and with access restricted to technical experts or their assistants only.
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.
- **Ingredients with limit values that require monitoring at the workplace:**
103-11-7 2-ethylhexyl acrylate
short term value : 38 mg/m³, 5 ppm
long term value : 38 mg/m³, 5 ppm

CAS: 80-62-6 methyl methacrylate	
WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm
CAS: 141-32-2 n-butyl acrylate	
WEL	Short-term value: 26 mg/m ³ , 5 ppm Long-term value: 5 mg/m ³ , 1 ppm

- **DNELs**
80-62-6 methyl methacrylate :
Inhalative DNEL (poulation) 74.3 mg/m³ (long term - systemic effects)
105 mg/m³ (long term - local effects)
DNEL (worker) 210 mg/m³ (long term - systemic effects)
210 mg/m³ (long term - local effects)

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2020

Version number 1

Revision: 18.12.2020

Trade name: IKO Metatech Mortar L

(Contd. of page 4)

103-11-7 2-ethylhexyl acylate

 Dermal DNEL 242µg/cm² (long term and short term)

 Inhalative DNEL 37.5 mg/m³ (long term)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

Suitable respiratory protective device recommended.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.33 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Value for the permeation: Level ≤ 66 min.

· **For the permanent contact gloves made of the following materials are suitable:** Butyl rubber, BR

· **Not suitable are gloves made of the following materials:** Leather gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Use protective suit.

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **Appearance:**

Form:

Fluid

Colour:

Colourless

· **Odour:**

Ester-like

· **Odour threshold:**

<1ppm

· **pH-value:**

Not determined.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2020

Version number 1

Revision: 18.12.2020

Trade name: **IKO Metatech Mortar L**

(Contd. of page 5)

- **Change in condition**
 - Melting point/freezing point:** Undetermined.
 - Initial boiling point and boiling range:** 100 °C
- **Flash point:** 9 °C
- **Flammability (solid, gas):** Not applicable.
- **Ignition temperature:** 430 °C
- **Decomposition temperature:** Not determined.
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
 - Lower:** 2.1 Vol %
 - Upper:** 12.5 Vol %
- **Oxidising properties** Not determined.
- **Vapour pressure at 20 °C:** 40 hPa
- **Density at 20 °C:** 0.93 g/cm³
- **Relative density** Not determined.
- **Vapour density** >1 (20°C)
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
 - Dynamic at 20 °C:** 1 mPas
 - Kinematic:** Not determined.
- **9.2 Other information** No further information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Reacts with peroxides and other radical forming substances.
Exothermic reaction.
Exothermic polymerisation.
- **10.4 Conditions to avoid** Keep away from heat and direct sunlight.
- **10.5 Incompatible materials:**
Reacts with peroxides.
Reacts with reducing agents.
Acids, bases and amines.
Reacts with acids, alkalis and oxidising agents.
- **10.6 Hazardous decomposition products:** None at a proper use of the product.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2020

Version number 1

Revision: 18.12.2020

Trade name: **IKO Metatech Mortar L**

(Contd. of page 6)

- **LD/LC50 values relevant for classification:**

- **ATE (Acute Toxicity Estimates)**

Oral	LD50	>3,051-7,500 mg/kg
Dermal	LD50	>28,571-66,667 mg/kg (rabbit)

- **CAS: 80-62-6 methyl methacrylate**

Oral	LD50	7,872 mg/kg (rat)
------	------	-------------------

- **CAS: 141-32-2 n-butyl acrylate**

Oral	LD50	900 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**
May cause an allergic skin reaction.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:**
80-62-6 methyl methacrylate
EC50/48h 69 mg/l (daphnia magna) (OECD 202)
EC50/72h >110 mg/l (Selenastrum capricornutum) (OECD201)
LC50/96h >79mg/l (Rainbow trout) (OECD 203)
- **12.2 Persistence and degradability** Easily biodegradable
- **Other information:** The product is easily biodegradable.
- **12.3 Bioaccumulative potential** Potential to bioaccumulate.
- **12.4 Mobility in soil** Groundwater can be contaminated.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2020

Version number 1

Revision: 18.12.2020


Trade name: IKO Metatech Mortar L

(Contd. of page 7)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal should be in accordance with applicable regional, national and local laws and regulations.
- **Uncleaned packaging:**
- **Recommendation:**
Packaging may be reused or recycled after cleaning.
Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

- | | | |
|---|--|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | <p style="margin-left: 20px;">UN1993</p> | |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA | <p style="margin-left: 20px;">UN1993 FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED)
FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED)</p> | |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG, IATA | <div style="text-align: center; margin-bottom: 10px;">  </div> <ul style="list-style-type: none"> · Class · Label | <p style="margin-left: 20px;">3 Flammable liquids.
3</p> |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA | <p style="margin-left: 20px;">II</p> | |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | <p style="margin-left: 20px;">No</p> | |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category | <p style="margin-left: 20px;">Warning: Flammable liquids.
33
F-E,<u>S-E</u>
B</p> | |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | <p style="margin-left: 20px;">Not applicable.</p> | |
| <ul style="list-style-type: none"> · Transport/Additional information: | <p style="margin-left: 20px;">Special provision 640D
5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml</p> | |
| <ul style="list-style-type: none"> · Transport category | <p style="margin-left: 20px;">2</p> | |

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2020

Version number 1

Revision: 18.12.2020

Trade name: **IKO Metatech Mortar L**

(Contd. of page 8)

· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED), 3, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**
This product does not contain any SVHC's.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet (SDS) is calculated with a Calculation method based on CLP Annex I, parts 2 to 5.

- **Relevant phrases**
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H350 May cause cancer.
- H412 Harmful to aquatic life with long lasting effects.
- **Contact:** sds.europe@iko.com

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.12.2020

Version number 1

Revision: 18.12.2020

Trade name: IKO Metatech Mortar L

(Contd. of page 9)

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Carc. 1B: Carcinogenicity – Category 1B
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

GB