

Version number 1

Revision: 21.01.2020

| | .0 | Version number 1 | | |
|---|--|---|--|--|
| SECTION 1: Ic undertaking | dentification of | of the substance/ | mixture and c | of the company/ |
| · 1.1 Product identi | ifier | | | |
| · Trade name: IKC |) Tanetech E | BT | | |
| Sector of Use SU3 Industrial use | tified uses of the es: Uses of substa | substance or mixture nces as such or in prep domain (administratior | parations at industri | ial sites |
| craftsmen) SU19 Building and SU21 Consumer - Application of the | d construction wor uses: Private hous substance / the | k eholds / general public mixture | | , , |
| Liquid waterproofin | 0 | | | |
| 1.3 Details of the s Manufacturer/Sup IKO Europe nv d'Herbouvillekaai 8 B-2020 Antwerpen Belgium Tel.: +32 (0)3 248 3 E-mail: sds.europe | oplier: 0 30 00 | nety data sheet | | |
| 24; National Poisc 2566. NPIS & NPIC • 1.4 Emergency te United Kingdom Na | nformation Servic ons Information C C services are prov lephone number: ational Poisons Info pisons Information | e UK: England and Wa entre Ireland: +00 353 /ided exclusively for hea ormation Service (+44) Centre Tel: +353 1 809 | 3 (0) 1 837 9964 d althcare profession 844 892 0111 - 03 | or +00 353 (0) 1 809 hals working in NHS. |
| | | | | |
| SECTION 2: Ha | azards identifi | cation | | |
| · 2.1 Classification | of the substance | or mixture | | |
| | | tion (EC) No 1272/200 | | |
| | | liquid and vapour. | • | |
| | | allergy or asthma symp | otoms or breathing | difficulties if inhaled. |
| Skin Sens. 1 | H317 May cause | an allergic skin reactior | ٦. | |
| | • | aquatic life with long las | | |
| 2.2 Label element Labelling according The product is clas Hazard pictogram | ng to Regulation sified and labelled | (EC) No 1272/2008 according to the CLP r | egulation. | |
| | | | | |
| GHS02 GHS08 | | | | |
| · Signal word Dang | er | | | |
| Hazard-determinit benzotriazole deriv sebacate derivative | atives | of labelling: | | |
| aliphatic polyisocya 2-Ethylexyl (6 -isoc | | amate | | |
| (0 1000 | | | | (Contd. on page 2) |



Version number 1

Revision: 21.01.2020

Trade name: IKO Tanetech BT

Printing date 21.01.2020

| | (Contd. of page 1) |
|----------------------------------|--|
| | liyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate |
| | diisocyanate polymer |
| | ane-1,6-diamine |
| 4,4'-isopropy | /lidenediphenol |
| Hazard stat | ements |
| | nable liquid and vapour. |
| H334 May c | ause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H317 May c | ause an allergic skin reaction. |
| H412 Harmf | ul to aquatic life with long lasting effects. |
| Precautiona | ary statements |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition |
| | sources. No smoking. |
| P241 | Use explosion-proof electrical/ventilating/lighting equipment. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P284 | [In case of inadequate ventilation] wear respiratory protection. |
| P303+P361- | +P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin |
| | with water/shower. |
| P501 | Dispose of contents/container in accordance with local/regional/national/ |
| | international regulations. |
| Additional i | nformation: |
| | status ta constatus. Massi a constructiona a Hanstania a destructura |

EUH204 Contains isocyanates. May produce an allergic reaction.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

| CAS: 426822-87-9 | aliphatic polyisocyanate | 25-40% |
|--|--|----------|
| | Skin Sens. 1, H317 | |
| CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29 | 2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 | ≥10-<20% |
| CAS: 140921-24-0 ELINCS: 411-700-4 Reg.nr.: 01-0000015906-63 | 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl) ethyl)carbamate Skin Sens. 1, H317 | 5-10% |
| CAS: 108-65-6 EINECS: 203-603-9 | 2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 | 5-10% |
| CAS: 53880-05-0 NLP: 500-125-5 Reg.nr.: 01-2119488734-24 | Isophorone diisocyanate polymer Skin Sens. 1, H317; STOT SE 3, H335 | 2.5-5% |
| EC number: 918-668-5 Reg.nr.: 01-2119455851-35 | Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 | ≥1-<2.5% |
| CAS: 26488-60-8 EINECS: 247-735-5 | 2-Ethylexyl (6 -isocyanatohexyl)-carbamate Acute Tox. 3, H331 Resp. Sens. 1, H334 Skin Sens. 1B, H317; STOT SE 3, H335 Aquatic Chronic 3, H412 | ≥1-<2.5% |
| CAS: 41556-26-7 | Bis(1,2,,2,6,6-pentamethyl-4-piperidyl)sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317 | 0.3-0.4% |
| CAS: 82919-37-7 | methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317 | 0.3-0.4% |



Version number 1

Revision: 21.01.2020

Trade name: IKO Tanetech BT

Printing date 21.01.2020

| CAS: 104810-48-2 ELINCS: 400-830-7 | poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)- 5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω- hydroxy- Aquatic Chronic 2, H411 Skin Sens. 1, H317 | 0.3-0.4% |
|--|---|-------------|
| CAS: 104810-47-1 | poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)- 5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω- [3-[3-(2H- benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4- hydroxyphenyl]-1-oxopropoxy]- Aquatic Chronic 2, H411 Skin Sens. 1, H317 | ≥0.2-<0.25% |
| CAS: 4098-71-9 EINECS: 223-861-6 Reg.nr.: 01-2119490408-31 | 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 2, H330 Resp. Sens. 1, H334 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335 | 0.1-0.2% |
| CAS: 25620-58-0 EINECS: 247-134-8 | trimethylhexane-1,6-diamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1, H317 Aquatic Chronic 3, H412 | 0.1-0.2% |
| CAS: 1185-81-5 EINECS: 214-688-7 Reg.nr.: 01-2119841260-50 | dibutylbis(dodecyl)thiostannaan Muta. 2, H341; Repr. 1B, H360; STOT RE 1, H372 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1, H317 | 0.1% |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Not applicable.
- Not applicable.

No further relevant information available.

(Contd. on page 4)

⁻ GB

Version number 1

Revision: 21.01.2020

Trade name: IKO Tanetech BT

· 5.3 Advice for firefighters

Printing date 21.01.2020

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

\cdot 7.1 Precautions for safe handling

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). • Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from humidity and water. Keep container tightly sealed.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

| · Ingre | dients with limit values that require monitoring at the workplace: | |
|---------|--|--------------------|
| CAS: | 108-65-6 2-methoxy-1-methylethyl acetate | |
| WEL | Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk | |
| CAS: | 108-65-6 2-methoxy-1-methylethyl acetate | |
| WEL | Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk | |
| CAS: | 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate | |
| WEL | Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO | |
| | | (Contd. on page 5) |

GB



Version number 1

Revision: 21.01.2020

Trade name: IKO Tanetech BT

Printing date 21.01.2020

| | | (Contd. of page 4 |
|------------------|---|--|
| - | ith biological limit values | |
| | | 5,5-trimethylcyclohexyl isocyanate |
| | l creatinine/mol | |
| | m: urine | aariad ad avpaaura |
| | ing time: At the end of the p eter: isocyanate-derived dia | |
| | | uring the making were used as basis. |
| | | uning the making were used as basis. |
| 8.2 Exposure | controls ective equipment: | |
| | ective and hygienic measu | |
| | emove all soiled and contain | |
| | efore breaks and at the end | |
| | rotection: Not necessary in | |
| | hands: Solvent resistant g | |
| Material of gl | | |
| | | not only depend on the material, but also on further mark |
| | | o manufacturer. As the product is a preparation of sever |
| | | naterial can not be calculated in advance and has therefor |
| | prior to the application. | |
| | me of glove material | |
| | | ound out by the manufacturer of the protective gloves ar |
| has to be obse | | |
| Eye protectio | n: | |
| | | |
| (Tigentia) Tigh | tly sealed goggles | |
| | , | |
| | | |
| | | |
| SECTION 9 | : Physical and chemi | cal properties |
| . 9 1 Informati | on on basic physical and o | chamical properties |
| · Appearance: | in on basic physical and t | chemical properties |
| Form: | | Viscous |
| Colour: | | Different according to colouring |
| · Odour: | | Characteristic |
| · pH-value: | | Not determined. |
| · Change in co | ndition | |
| | g point and boiling range | e: 146 °C |
| · Flash point: | | 44 °C |
| · Ignition temp | erature: | 315 °C |
| · Auto-ignition | | Product is not selfigniting. |
| Explosive pro | | Product is not explosive. However, formation of |
| | • | |

| · Explosive properties. | explosive air/vapour mixtures are possible. |
|--|---|
| Explosion limits: | |
| Lower: | 1.5 Vol % |
| Upper: | 10.8 Vol % |
| Vapour pressure at 20 °C: | 3.4 hPa |
| Density at 20 °C: | 1.4 g/cm ³ |
| Solubility in / Miscibility with | |
| water: | Insoluble. |
| · Viscosity: | |
| Dynamic at 25 °C: | 6000-9000 mPas |

(Contd. on page 6)

GB

Version number 1

Revision: 21.01.2020

Trade name: IKO Tanetech BT

· Solvent content:

Printing date 21.01.2020

VOC (EC)

VOC limit value (cat A/i) 500 g/L 2010. Product contains 220 g/L.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Keep away from oxidising agents and strongly alkaline and strongly acidic materials. Uncontrolled exothermic reactions occur with amines and alcohols. The product reacts slowly with water resulting in evolution of carbon dioxide.

· 10.6 Hazardous decomposition products:

Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.

| • | - | / Estimates) |
|-----------|-------------|---|
| nhalative | LC50/4 h | >27.8 mg/l |
| CAS: 108- | ·65-6 2-me | thoxy-1-methylethyl acetate |
| Dral | LD50 | 8,532 mg/kg (rat) |
| nhalative | LC50/4 h | 35.7 mg/l (rat) |
| CAS: 1409 | 921-24-0 1 | ,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate |
| Dral | LD50 | >2,000 mg/kg (rat) |
| Dermal | LD50 | >2,000 mg/kg (rat) |
| CAS: 108- | ·65-6 2-me | thoxy-1-methylethyl acetate |
| Dral | LD50 | 8,532 mg/kg (rat) |
| nhalative | LC50/4 h | 35.7 mg/l (rat) |
| Solvent n | aphtha (p | etroleum), light arom. |
| Dral | LD50 | >6,800 mg/kg (rat) |
| Dermal | LD50 | >3,400 mg/kg (rab) |
| nhalative | LC50/4 h | >10.2 mg/l (rat) |
| CAS: 2648 | 38-60-8 2- | Ethylexyl (6 -isocyanatohexyl)-carbamate |
| Dral | LD50 | >2,500 mg/kg (rat) |
| nhalative | LC50/4 h | 0.521 mg/l (rat) |
| CAS: 2562 | 20-58-0 tri | methylhexane-1,6-diamine |
| Dral | LD50 | 900 mg/kg (rat) |
| CAS: 118 | 5-81-5 dib | utylbis(dodecyl)thiostannaan |
| Dral | LD50 | >2,000 mg/kg (rat) |
| Dermal | LD50 | 1,500 mg/kg (rab) |



(Contd. of page 5)

IKO

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision: 21.01.2020

(Contd. of page 6)

Trade name: IKO Tanetech BT

· Primary irritant effect:

Printing date 21.01.2020

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Splashes in the eyes may cause irritation and reversible local damage.
- · Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

Aquatic toxicity:

CAS: 140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

Inhalative LC50 193 mg/l (daphnia)

316 mg/l (fish)

CAS: 26488-60-8 2-Ethylexyl (6 -isocyanatohexyl)-carbamate

Inhalative LC50 >100 mg/l (fish) (96h)

EC50 >100 mg/l (daphnia) (48h)

CAS: 1185-81-5 dibutylbis(dodecyl)thiostannaan

EC50 0.11 mg/l (daphnia)

· 12.2 Persistence and degradability No further relevant information available.

- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:
- Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision: 21.01.2020

(Contd. of page 7)

Trade name: IKO Tanetech BT

Printing date 21.01.2020

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.


| SECTION 14: Transport informati | on |
|---|--|
| · 14.1 UN-Number · ADR, IMDG, IATA | UN1866 |
| · 14.2 UN proper shipping name · ADR · IMDG · IATA | UN 1866, RESIN SOLUTION, 3, III, (D/E) UN 1866, Resin solution, 3, III, (44°C c.c.) Transport in accordance with 2.3.2.5 of the IMDC code. RESIN SOLUTION |
| · 14.3 Transport hazard class(es) | |
| · ADR, IMDG, IATA | |
| · Class · Label | 3 Flammable liquids. 3 |
| · 14.4 Packing group · ADR, IMDG | 111 |
| • 14.5 Environmental hazards: • Marine pollutant: | No |
| 14.6 Special precautions for user Stowage Category | Warning: Flammable liquids. A |
| 14.7 Transport in bulk according to Ann of Marpol and the IBC Code | ex II Not applicable. |
| · Transport/Additional information: | |
| ADR Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| Transport category Tunnel restriction code | 3 D/E |
| IMDG Limited quantities (LQ) Excepted quantities (EQ) | 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| | |

(Contd. on page 9)

Revision: 21.01.2020

Trade name: IKO Tanetech BT

(Contd. of page 8)





Printing date 21.01.2020

Version number 1



Printing date 21.01.2020

Version number 1

Revision: 21.01.2020

Trade name: IKO Tanetech BT

| | (Contd. of page |
|---|-----------------|
| LC50: Lethal concentration, 50 percent | |
| LD50: Lethal dose, 50 percent | |
| PBT: Persistent, Bioaccumulative and Toxic | |
| SVHC: Substances of Very High Concern | |
| vPvB: very Persistent and very Bioaccumulative | |
| Flam. Liq. 3: Flammable liquids – Category 3 | |
| Acute Tox. 4: Acute toxicity - oral – Category 4 | |
| Acute Tox. 2: Acute toxicity - inhalation – Category 2 | |
| Acute Tox. 3: Acute toxicity - inhalation – Category 3 | |
| Skin Corr. 1B: Skin corrosion/irritation – Category 1B | |
| Skin Irrit. 2: Skin corrosion/irritation – Category 2 | |
| Eye Dam. 1: Serious eye damage/eye irritation – Category 1 | |
| Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 | |
| Resp. Sens. 1: Respiratory sensitisation – Category 1 | |
| Skin Sens. 1: Skin sensitisation – Category 1 | |
| Skin Sens. 1B: Skin sensitisation – Category 1B | |
| Muta. 2: Germ cell mutagenicity – Category 2 | |
| Repr. 1B: Reproductive toxicity – Category 1B | |
| STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 | |
| STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 | |
| Asp. Tox. 1: Aspiration hazard – Category 1 | |
| Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 | |
| Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 | |
| Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 | |
| Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 | |
| * Data compared to the previous version altered. | |