

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2020



Version number 1

Revision: 18.02.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- Trade name: **IKO Tanetech Bitumen Primer**
- UFI: 6CUK-V8SV-U00G-62GV
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 - SU21 Consumer uses: Private households / general public / consumers
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU19 Building and construction work
- **Application of the substance / the mixture** Adherence primer for Tanetech.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 - IKO Europe nv
 - d'Herbouvillekaai 80
 - B-2020 Antwerpen
 - Belgium
 - Tel.: +32 (0)3 248 30 00
 - E-mail: sds.europe@iko.com
- **Further information obtainable from:**
 - National Poisons Information Service UK: England and Wales: 0845 4647 Scotland: 08454 24 24 24;
 - National Poisons Information Centre Ireland: +00 353 (0) 1 837 9964 or +00 353 (0) 1 809 2566. NPIS & NPIC services are provided exclusively for healthcare professionals working in NHS.
- **1.4 Emergency telephone number:**
 - United Kingdom National Poisons Information Service (+44) 844 892 0111 - 0344 892 0111
 - Ireland National Poisons Information Centre Tel: +353 1 8092566
 - Emergency call only for healthcare professionals

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 - Flam. Liq. 3 H226 Flammable liquid and vapour.
 - Eye Irrit. 2 H319 Causes serious eye irritation.
 - STOT SE 3 H336 May cause drowsiness or dizziness.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 - The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**
 -  
 - GHS02 GHS07
- **Signal word** Warning
- **Hazard-determining components of labelling:**
 - n-butyl acetate
- **Hazard statements**
 - H226 Flammable liquid and vapour.

(Contd. on page 2)



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2020

Version number 1

Revision: 18.02.2020

Trade name: **IKO Tanetech Bitumen Primer**

(Contd. of page 1)

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 123-86-4	n-butyl acetate	50-75%
EINECS: 204-658-1	Flam. Liq. 3, H226	
Reg.nr.: 01-2119485493-29	STOT SE 3, H336	
Reg.nr.: 01-2119513212-58	Silquest A187 Consisting of: 2530-83-8 [3-(2,3-epoxypropoxy)propyl] trimethoxysilane (50-100%) Eye Dam. 1, H318	1%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Generally the product does not irritate the skin.

- **After eye contact:** Rinse opened eye for several minutes under running water.

- **After swallowing:** If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2020

Version number 1

Revision: 18.02.2020

Trade name: IKO Tanetech Bitumen Primer

(Contd. of page 2)

- **5.2 Special hazards arising from the substance or mixture**
Not applicable.
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 123-86-4 n-butyl acetate

WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
-----	---

- **Additional information:** The lists valid during the making were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment:**
- **General protective and hygienic measures:** Wash hands before breaks and at the end of work.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Protection of hands:** Solvent resistant gloves
- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2020

Version number 1

Revision: 18.02.2020

Trade name: **IKO Tanetech Bitumen Primer**

(Contd. of page 3)

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **Appearance:**

Form:	Fluid
Colour:	Light yellow
Odour:	Characteristic
pH-value:	Not determined.

- **Change in condition**

Initial boiling point and boiling range: 185 °C

- **Flash point:** 24 °C
- **Ignition temperature:** 370 °C
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
 - Lower:** 1.2 Vol %
 - Upper:** 7.5 Vol %
- **Vapour pressure at 20 °C:** 10.7 hPa
- **Density at 20 °C:** 0.98 g/cm³
- **Solubility in / Miscibility with water:** Insoluble.
- **organic solvents:** Miscible with many organic solvents.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic at 20 °C:** 16 s (DIN 53211/4)
- **Solvent content:**
 - VOC (EC)** VOC limit value (cat A/h) 750 g/L 2010.
Product contains 670 g/L.
- **9.2 Other information** No further information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2020

Version number 1

Revision: 18.02.2020

Trade name: **IKO Tanetech Bitumen Primer**

(Contd. of page 4)

• **10.6 Hazardous decomposition products:**

Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.

SECTION 11: Toxicological information

• **11.1 Information on toxicological effects**

• **Acute toxicity** Based on available data, the classification criteria are not met.

• **LD/LC50 values relevant for classification:**

CAS: 123-86-4 n-butyl acetate

Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

• **Primary irritant effect:**

• **Skin corrosion/irritation** Based on available data, the classification criteria are not met.

• **Serious eye damage/irritation**

Causes serious eye irritation.

• **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

• **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

• **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

• **Carcinogenicity** Based on available data, the classification criteria are not met.

• **Reproductive toxicity** Based on available data, the classification criteria are not met.

• **STOT-single exposure**

May cause drowsiness or dizziness.

• **STOT-repeated exposure** Based on available data, the classification criteria are not met.

• **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

• **12.1 Toxicity**

• **Aquatic toxicity:**

CAS: 123-86-4 n-butyl acetate

Inhalative	LC50	18 mg/l (fish) (96h)
	EC50	44 mg/l (daphnia)

• **12.2 Persistence and degradability** No further relevant information available.

• **12.3 Bioaccumulative potential** No further relevant information available.

• **12.4 Mobility in soil** No further relevant information available.

• **Additional ecological information:**

• **General notes:**

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

• **12.5 Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2020

Version number 1

Revision: 18.02.2020


Trade name: **IKO Tanetech Bitumen Primer**

(Contd. of page 5)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG · IATA | <ul style="list-style-type: none"> UN1866 Void |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | <ul style="list-style-type: none"> UN1866 RESIN SOLUTION UN 1866, Resin solution, 3, III,(27°C c.c.) RESIN SOLUTION Void |
| <ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR, IMDG | <div style="text-align: center;">  </div> <ul style="list-style-type: none"> · Class · Label |
| <ul style="list-style-type: none"> · IATA · Class | <ul style="list-style-type: none"> 3 Flammable liquids. 3 Void |
| <ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG · IATA | <ul style="list-style-type: none"> III Void |
| <ul style="list-style-type: none"> · 14.5 Environmental hazards: · Marine pollutant: | <ul style="list-style-type: none"> No |
| <ul style="list-style-type: none"> · 14.6 Special precautions for user · Danger code (Kemler): · Stowage Category | <ul style="list-style-type: none"> Warning: Flammable liquids. 30 A |
| <ul style="list-style-type: none"> · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | <ul style="list-style-type: none"> Not applicable. |
| <ul style="list-style-type: none"> · Transport/Additional information: | <hr style="border-top: 1px dashed red;"/> <ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) |
| <ul style="list-style-type: none"> · Transport category | <ul style="list-style-type: none"> 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 |

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 18.02.2020

Version number 1

Revision: 18.02.2020

Trade name: IKO Tanetech Bitumen Primer

(Contd. of page 6)

· Tunnel restriction code	D/E
· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed
- **Seveso category P5c FLAMMABLE LIQUIDS**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**
This product does not contain any SVHC's.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H226 Flammable liquid and vapour.
H318 Causes serious eye damage.
H336 May cause drowsiness or dizziness.
- **Contact:** sds.europe@iko.com
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 3: Flammable liquids – Category 3
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. on page 8)



Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 18.02.2020

Version number 1

Revision: 18.02.2020

Trade name: IKO Tanetech Bitumen Primer

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. of page 7)

· * **Data compared to the previous version altered.**

GB