


Version number 1

Revision: 20.02.2020





Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 20.02.2020

Version number 1

Revision: 20.02.2020

Trade name: IKO Tanetech Detail

	(Contd. of page 1)
aliphatic poly	risocyanate
dibutylbis(do	decyl)thiostannaan
3-isocyanato	methyl-3,5,5-trimethylcyclohexyl isocyanate
Isophorone of	diisocyanate polymer
Hazard state	
H226 Flamm	hable liquid and vapour.
H332 Harmf	
H334 May ca	ause allergy or asthma symptoms or breathing difficulties if inhaled.
	ause an allergic skin reaction.
	amage fertility or the unborn child.
	ul to aquatic life with long lasting effects.
	iry statements
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing
	protection.
P285	In case of inadequate ventilation wear respiratory protection.
	P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water [or shower].
P501	Dispose of contents/container in accordance with local/regional/national/
	international regulations.
· Additional in	•
	ntains isocyanates. May produce an allergic reaction.
	itains isocyanates. May produce an allergic reaction.

Restricted to professional users.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

CAS: 426822-87-9	aliphatic polyisocyanate	25-40%
	Skin Sens. 1, H317	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	≥10-<20%
EINECS: 203-603-9	Flam. Liq. 3, H226	
0	STOT SÉ 3, H336	
CAS: 140921-24-0	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)	5-10%
ELINCS: 411-700-4	ethyl)carbamate	
	Skin Sens. 1, H317	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	5-10%
EINECS: 203-603-9	Flam. Liq. 3, H226	
CAS: 26488-60-8	2-Ethylexyl (6 -isocyanatohexyl)-carbamate	2.5-5%
EINECS: 247-735-5	Acute Tox. 3, H331	
	Resp. Sens. 1, H334	
	Skin Sens. 1B, H317; STOT SE 3, H335	
	Aquatic Chronic 3, H412	
CAS: 53880-05-0	Isophorone diisocyanate polymer	2.5-5%
NLP: 500-125-5	Skin Sens. 1, H317; STOT SE 3, H335	
Reg.nr.: 01-2119488734-24		
EC number: 918-668-5	Solvent naphtha (petroleum), light arom.	≥1-<2.5%
Reg.nr.: 01-2119455851-35	Flam. Liq. 3, H226	
	Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411	
	STOT SE 3, H335-H336	

IKO

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Revision: 20.02.2020

Trade name: IKO Tanetech Detail

Printing date 20.02.2020

CAS: 2530-83-8	[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	ntd. of pag 0.5-1%
EINECS: 219-784-2 Reg.nr.: 01-2119513212-58	Flam. Liq. 3, H226	
CAS: 1185-81-5 EINECS: 214-688-7 Reg.nr.: 01-2119841260-50	dibutylbis(dodecyl)thiostannaan Muta. 2, H341; Repr. 1B, H360; STOT RE 1, H372 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1, H317	0.3%
CAS: 4098-71-9 EINECS: 223-861-6 Reg.nr.: 01-2119490408-31	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 2, H330 Resp. Sens. 1, H334 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.1-0.29
CAS: 25620-58-0 EINECS: 247-134-8	trimethylhexane-1,6-diamine Skin Corr. 1B, H314; Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Sens. 1, H317 Aquatic Chronic 3, H412	0.1-0.29
CAS: 41556-26-7	Bis(1,2,,2,6,6-pentamethyl-4-piperidyl)sebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	0.1-0.29
CAS: 82919-37-7	methyl 1,2,2,6,6-pentamethyl-4-piperidylsebacate Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Skin Sens. 1, H317	0.1-0.29
CAS: 104810-48-2 ELINCS: 400-830-7	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5- (1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω- hydroxy- Aquatic Chronic 2, H411 Skin Sens. 1, H317	0.1-0.29
CAS: 80-05-7 EINECS: 201-245-8 Reg.nr.: 01-2119457856-23	4,4'-isopropylidenediphenol Repr. 1B, H360F Eye Dam. 1, H318 Skin Sens. 1, H317; STOT SE 3, H335	0.1-0.2%
CAS: 104810-47-1	poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5- (1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-[3-[3- (2H- benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4- hydroxyphenyl]-1-oxopropoxy]- Aquatic Chronic 2, H411 Skin Sens. 1, H317	0.1-0.2%

CAS: 80-05-7 4,4'-isopropylidenediphenol

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)

⁻ GB



Version number 1

Revision: 20.02.2020

Trade name: IKO Tanetech Detail

(Contd. of page 3) • **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Printing date 20.02.2020

- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Not applicable.
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- \cdot 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling No special precautions are necessary if used correctly. • Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep container tightly sealed.

SECTION 8: Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

 Ingredients with limit values that require monitoring at the workplace: 		
CAS:	108-65-6 2-methoxy-1-methylethyl acetate	
	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk	
CAS:	108-65-6 2-methoxy-1-methylethyl acetate	
	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk	
•	(Contd. on page 5)	



Printing date 20.02.2020

Upper:

Version number 1

Revision: 20.02.2020

Trade name: IKO Tanetech Detail

CAS: 1008 71 0 2 is accurate moth	(Contd. of page hyl-3,5,5-trimethylcyclohexyl isocyanate		
WEL Short-term value: 0.07 mg/m ³			
Long-term value: 0.07 mg/m ³			
Sen; as -NCO			
Ingredients with biological limit v			
	alues. hyl-3,5,5-trimethylcyclohexyl isocyanate		
BMGV 1 µmol creatinine/mol	iyi-3,3,3-ti illetti yicyclonexyi isocyanate		
Medium: urine			
Sampling time: At the end o	f the period od exposure		
Parameter: isocyanate-deriv			
Additional information: The lists v	alid during the making were used as basis.		
8.2 Exposure controls			
Personal protective equipment:			
General protective and hygienic r	neasures:		
Immediately remove all soiled and c			
Wash hands before breaks and at the	he end of work.		
Respiratory protection:			
	ed. In case of brief exposure or low pollution use respiratory fill		
	intensive or longer exposure use self-contained respirato		
protective device.	tent aleves		
 Protection of hands: Solvent resis Material of gloves 	tant gioves		
	does not only depend on the material, but also on further mar		
	urer to manufacturer. As the product is a preparation of sevel		
	ove material can not be calculated in advance and has therefo		
to be checked prior to the applicatio			
Penetration time of glove materia			
	o be found out by the manufacturer of the protective gloves a		
has to be observed.			
Eye protection:			
Tightly sealed goggles			
rightiy sealed goggles			
SECTION 9: Physical and cl	nemical properties		
9.1 Information on basic physical	and chemical properties		
Appearance:	. <i>a</i>		
Form:	Viscous		
Colour:	Grey		
Odour:	Characteristic		
· pH-value:	Not determined.		
Change in condition			
Initial boiling point and boiling			
Flash point:	44 °C		
Flash point: Ignition temperature:	44 ℃ 315 ℃		
Flash point: Ignition temperature: Auto-ignition temperature:	44 °C 315 °C Product is not selfigniting.		
Flash point: Ignition temperature:	44 °C 315 °C Product is not selfigniting. Product is not explosive. However, formation of		
Flash point: Ignition temperature: Auto-ignition temperature: Explosive properties:	44 °C 315 °C Product is not selfigniting.		
 Flash point: Ignition temperature: Auto-ignition temperature: Explosive properties: Explosion limits: 	44 °C 315 °C Product is not selfigniting. Product is not explosive. However, formation of explosive air/vapour mixtures are possible.		
Flash point: Ignition temperature: Auto-ignition temperature: Explosive properties:	44 °C 315 °C Product is not selfigniting. Product is not explosive. However, formation		

10.8 Vol %

(Contd. on page 6)

GB

IKO

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.02.2020

Version number 1

Revision: 20.02.2020

(Contd. of page 5)

Trade name: IKO Tanetech Detail

· Vapour	pressure	at 20 °C:
----------	----------	-----------

 Density at 20 °C:
 Solubility in / Miscibility with water:

 Viscosity: Dynamic at 20 °C: Kinematic:
 Solvent content:

· 9.2 Other information

VOC (EC)

1.15 g/cm³ Insoluble.

3.4 hPa

15000 mPas Not determined.

VOC limit value (cat A/i) 500 g/L 2010. Product contains 380 g/L. No further information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.2 Peoplicities of bezordous reactions.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- 10.6 Hazardous decomposition products:

Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h >10.9 mg/l

CAS: 108-	-65-6 2-me	ethoxy-1-methylethyl acetate
Oral	LD50	8,532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)
CAS: 140	921-24-0 1	,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
CAS: 108-	-65-6 2-me	ethoxy-1-methylethyl acetate
Oral	LD50	8,532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)
CAS: 264	88-60-8 2-	Ethylexyl (6 -isocyanatohexyl)-carbamate
Oral	LD50	>2,500 mg/kg (rat)
Inhalative	LC50/4 h	0.521 mg/l (rat)
Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
		(Contd. on pag



Revision: 20.02.2020

Printing date 20.02.2020

Version number 1

Trade name: IKO Tanetech Detail

	/	(Contd. of page
CAS: 253	0-83-8 [3-(2,3-epoxypropoxy)propyl]trimethoxysilane
Oral	LD50	8,025 mg/kg (rat)
Dermal	LD50	4,250 mg/kg (rab)
Inhalative	LC50/4 h	>5.3 mg/l (rat)
CAS: 118	5-81-5 dib	utylbis(dodecyl)thiostannaan
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	1,500 mg/kg (rab)
CAS: 256	20-58-0 tri	methylhexane-1,6-diamine
Oral	LD50	900 mg/kg (rat)
CAS: 80-0)5-7 4,4'-is	opropylidenediphenol
Oral	LD50	3,250 mg/kg (rat)
Dermal	LD50	3,000 mg/kg (rabbit)
Primary in	ritant effe	ect:
		ation Based on available data, the classification criteria are not met.
		e/irritation
		may cause irritation and reversible local damage.
		sensitisation asthma symptoms or breathing difficulties if inhaled.
		ic skin reaction.
		nogenity, mutagenicity and toxicity for reproduction)
	•	is the provide large state of the section of the sector of

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- May damage fertility or the unborn child.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 140921-24-0 1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

Inhalative LC50 193 mg/l (daphnia)

316 mg/l (fish)

CAS: 26488-60-8 2-Ethylexyl (6 -isocyanatohexyl)-carbamate

Inhalative LC50 >100 mg/l (fish) (96h)

EC50 >100 mg/l (daphnia) (48h)

CAS: 1185-81-5 dibutylbis(dodecyl)thiostannaan

EC50 0.11 mg/l (daphnia)

· 12.2 Persistence and degradability No further relevant information available.

- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.

(Contd. on page 8)

[—] GB

Version number 1

Revision: 20.02.2020

Trade name: IKO Tanetech Detail

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Printing date 20.02.2020

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informat	tion
· 14.1 UN-Number · ADR, IMDG, IATA	UN1866
 · 14.2 UN proper shipping name · ADR 	UN 1866, RESIN SOLUTION, 3, III, (D/E) exemption according 2.2.3.1.5.
· IMDG	UN 1866, Resin solution, 3, III, (44°C c.c.) Transport in accordance with 2.3.2.5 of the IMDG code.
	RESIN SOLUTION
 14.3 Transport hazard class(es) 	
· ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
 • 14.5 Environmental hazards: • Marine pollutant: 	No
 14.6 Special precautions for user 	Warning: Flammable liquids.
 14.7 Transport in bulk according to Ann of Marpol and the IBC Code 	nex II Not applicable.
· Transport/Additional information:	
 ADR Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
 Transport category 	3
Tunnel restriction code	D/E
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3

(Contd. on page 9)

GB



(Contd. of page 7)

Version number 1

Revision: 20.02.2020

Trade name: IKO Tanetech Detail

Printing date 20.02.2020

(Contd. of page 8)

SECTION 15: Regulatory information · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Directive 2012/18/EU · Named dangerous substances - ANNEX I None of the ingredients is listed • Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 30 · Regulation (EU) No 649/2012 CAS: 1185-81-5 dibutylbis(dodecyl)thiostannaan Annex I Part 1 · National regulations: · Other regulations, limitations and prohibitive regulations Substances of very high concern (SVHC) according to REACH, Article 57 CAS: 80-05-7 4,4'-isopropylidenediphenol · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out. **SECTION 16: Other information** This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. Relevant phrases H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H330 Fatal if inhaled. H331 Toxic if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H341 Suspected of causing genetic defects. H360 May damage fertility or the unborn child. H360F May damage fertility.

- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.
- · Contact: sds.europe@iko.com

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 10)



Printing date 20.02.2020

Version number 1

Revision: 20.02.2020

Trade name: IKO Tanetech Detail

	(Contd. of page 9)
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
PBT: Persistent, Bioaccumulative and Toxic	
SVHC: Substances of Very High Concern	
vPvB: very Persistent and very Bioaccumulative	
Flam. Lig. 3: Flammable liquids – Category 3	
Acute Tox. 4: Acute toxicity - dermal – Category 4	
Acute Tox. 2: Acute toxicity - inhalation – Category 2	
Acute Tox. 3: Acute toxicity - inhalation – Category 3	
Skin Corr. 1B: Skin corrosion/irritation – Category 1B	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Catego	
Eye Irrit. 2: Serious eye damage/eye irritation – Categor	y 2
Resp. Sens. 1: Respiratory sensitisation – Category 1	
Skin Sens. 1: Skin sensitisation – Category 1	
Skin Sens. 1B: Skin sensitisation – Category 1B	
Muta. 2: Germ cell mutagenicity – Category 2	
Repr. 1B: Reproductive toxicity – Category 1B	
Repr. 1B: Reproductive toxicity – Category 1B	
STOT SE 3: Specific target organ toxicity (single exposu	
STOT RE 1: Specific target organ toxicity (repeated exp	osure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1	
Aquatic Acute 1: Hazardous to the aquatic environment	
Aquatic Chronic 1: Hazardous to the aquatic environment	
Aquatic Chronic 2: Hazardous to the aquatic environment	
Aquatic Chronic 3: Hazardous to the aquatic environme	
• * Data compared to the previous version a	Itered.
· · ·	GB