




**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** ***IKOpro Aluminium Paint***
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
*No further relevant information available.*
- **Application of the substance / the mixture** *Aluminium Reflective Roof Paint*
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
IKO PLC  
Appley Lane North  
Appley Bridge  
Wigan  
Lancashire  
WN6 9AB
- **Further information obtainable from:**  
uktechnical@iko.com
- **1.4 Emergency telephone number:** +44 1257 256864 Opening Times: 0900 - 1700 Monday to Friday

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
*Flam. Liq. 3 H226 Flammable liquid and vapour.*  
*Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.*  
*STOT SE 3 H336 May cause drowsiness or dizziness.*
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**  
*R10-66-67: Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.*
- **Information concerning particular hazards for human and environment:**  
*The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.*
- **Classification system:**  
*The classification is according to the latest editions of the EU-lists, and extended by company and literature data.*
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
*The product is classified and labelled according to the CLP regulation.*
- **Hazard pictograms**  
    
GHS02   GHS07   GHS08
- **Signal word** *Danger*
- **Hazard-determining components of labelling:**  
*hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates*
- **Hazard statements**  
*H226 Flammable liquid and vapour.*  
*H336 May cause drowsiness or dizziness.*  
*H304 May be fatal if swallowed and enters airways.*
- **Precautionary statements**  
*P102                      Keep out of reach of children.*  
*P210                      Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

(Contd. on page 2)

**Trade name: IKOpro Aluminium Paint**

(Contd. of page 1)

- P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**  
 EUH066 Repeated exposure may cause skin dryness or cracking.

**SECTION 3: Composition/information on ingredients**

- **3.2 Chemical characterization: Mixtures**  
 · **Description:** Mixture of substances listed below with nonhazardous additions.

 · **Dangerous components:**

EC number: 919-857-5 Reg.nr.: 01-2119463258-33	hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates Xn R65 R10-66-67 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	25-50%
	Aluminiumpasta F R11 R66 Flam. Sol. 1, H228	10-25%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**  
 · **After inhalation:** Supply fresh air; consult doctor in case of complaints.  
 · **After skin contact:** Generally the product does not irritate the skin.  
 · **After eye contact:** Rinse opened eye for several minutes under running water.  
 · **After swallowing:** If symptoms persist consult doctor.  
 · **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.  
 · **4.3 Indication of any immediate medical attention and special treatment needed**  
 No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**  
 · **Suitable extinguishing agents:**  
 CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.  
 · **For safety reasons unsuitable extinguishing agents:** Water with full jet  
 · **5.2 Special hazards arising from the substance or mixture** No further relevant information available.  
 · **5.3 Advice for firefighters**  
 · **Protective equipment:** No special measures required.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
 Wear protective equipment. Keep unprotected persons away.  
 · **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Trade name: **IKOpro Aluminium Paint**

(Contd. of page 2)

- **6.3 Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*
- **6.4 Reference to other sections**  
*See Section 7 for information on safe handling.*  
*See Section 8 for information on personal protection equipment.*  
*See Section 13 for disposal information.*

## **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** *No special precautions are necessary if used correctly.*
- **Information about fire - and explosion protection:**  
*Keep ignition sources away - Do not smoke.*  
*Protect against electrostatic charges.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** *Store in a cool location.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:**  
*Keep container tightly sealed.*  
*Protect from humidity and water.*
- **7.3 Specific end use(s)** *No further relevant information available.*

## **SECTION 8: Exposure controls/personal protection**

- **Additional information about design of technical facilities:** *No further data; see item 7.*
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**  
*The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*
- **Additional information:** *The lists valid during the making were used as basis.*
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:** *Wash hands before breaks and at the end of work.*
- **Respiratory protection:** *Not required.*
- **Protection of hands:**  
*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*  
*Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*  
*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*
- **Material of gloves**  
*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*
- **Penetration time of glove material**  
*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

(Contd. on page 4)

Trade name: **IKOpro Aluminium Paint**

(Contd. of page 3)

· Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· Appearance:

· Form:	Fluid
· Colour:	Silver grey
· Odour:	Petroleum-like
· pH-value:	Not determined.

· Change in condition

· Boiling point/Boiling range:	130 °C
· Flash point:	36 °C
· Ignition temperature:	450 °C
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
· Lower:	0.5 Vol %
· Upper:	7.0 Vol %
· Vapour pressure at 20 °C:	3 hPa
· Density at 20 °C:	0.93 g/cm <sup>3</sup>
· Solubility in / Miscibility with water:	Insoluble.
· organic solvents:	Miscible with many organic solvents.
· Solvent content:	
· VOC (EC)	VOC limit value (cat A/i) 500 g/L 2010. Product contains 430 g/L.

## SECTION 10: Stability and reactivity

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: Stable at environment temperature.

· 10.3 Possibility of hazardous reactions Explosive reaction with water.

· 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products:

Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.

## SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity:

· LD/LC50 values relevant for classification:

hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rab)

(Contd. on page 5)

**Trade name: IKOpro Aluminium Paint**

(Contd. of page 4)

Inhalative LC50/4 h >4951 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:**

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

**SECTION 12: Ecological information**

· **12.1 Toxicity**

· **Aquatic toxicity:** No further relevant information available.

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Other adverse effects** No further relevant information available.

**SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

**SECTION 14: Transport information**

· **14.1 UN-Number**

· **ADR, IMDG**

UN1268

· **14.2 UN proper shipping name**

· **ADR**

UN 1268, PETROLEUM PRODUCTS, N.O.S.

· **IMDG**

UN 1268, Petroleum products n.o.s., 3, III, (35 °C c.c.)

· **14.3 Transport hazard class(es)**

· **ADR, IMDG**



· **Class**

3 Flammable liquids.

· **Label**

3

· **14.4 Packing group**

· **ADR, IMDG**

III

(Contd. on page 6)

**Trade name: IKOpro Aluminium Paint**

(Contd. of page 5)

· <b>14.5 Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b>	Warning: Flammable liquids.
· <b>Danger code (Kemler):</b>	30
· <b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b>	3
· <b>Tunnel restriction code</b>	D/E
· <b>UN "Model Regulation":</b>	UN1263, PAINT RELATED MATERIAL, 3, III

**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- R10 Flammable.
- R11 Highly flammable.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** Product safety department

**Contact:**

Bert Bergé  
e-mail : bert.berge@iko.eu

**Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Liq. 3: Flammable liquids, Hazard Category 3

(Contd. on page 7)

**Trade name: IKOpro Aluminium Paint**

(Contd. of page 6)

*Flam. Sol. 1: Flammable solids, Hazard Category 1*

*STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3*

*Asp. Tox. 1: Aspiration hazard, Hazard Category 1*

· Version History.

Version 1.0 June 1st 2015 New release for Classification, Labelling Packaging Regulations

Version 2 January 2017 - Revised Information added