

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Wickes - Metal and Concrete Bitumen Paint
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU21 Consumer uses: Private households / general public / consumers
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Bitumen coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 IKO Europe nv
 d'Herbouvillekaai 80
 B-2020 Antwerpen
 Belgium
 Tel.: 00800 32 04 32
 E-mail: Wim.Verstraeten@iko.com
- **Further information obtainable from:**
 UK: 0844 412 7228
 Ireland : 01885 5090
- **1.4 Emergency telephone number:** not available

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 Flam. Liq. 3 H226 Flammable liquid and vapour.
 STOT SE 3 H336 May cause drowsiness or dizziness.
 STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.
 Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
 The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
 hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates
 Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)
- **Hazard statements**
 H226 Flammable liquid and vapour.
 H336 May cause drowsiness or dizziness.
 H372 Causes damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
 P102 Keep out of reach of children.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

Trade name: Wickes - Metal and Concrete Bitumen Paint

(Contd. of page 1)

P303+P361+P353 *IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*

P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

Additional information:

EUH066 *Repeated exposure may cause skin dryness or cracking.*

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of complex substances derived from petroleum and aromatic hydrocarbons.

Dangerous components:

EC number: 919-857-5 Reg.nr.: 01-2119463258-33	hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	25-30%
EC number: 919-446-0 Reg.nr.: 01-2119458049-33	Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%) Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	10-<25%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture Not applicable.

5.3 Advice for firefighters

Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

Trade name: Wickes - Metal and Concrete Bitumen Paint

(Contd. of page 2)

- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Keep away from heat and direct sunlight.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **DNELs**

hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates

Inhalative	Grenswaarde	871 mg/m ³ (human)
------------	-------------	-------------------------------

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)

Inhalative	Grenswaarde	330 mg/m ³ (human)
------------	-------------	-------------------------------

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Not necessary if room is well-ventilated.
- **Protection of hands:** Solvent resistant gloves
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

Trade name: Wickes - Metal and Concrete Bitumen Paint

(Contd. of page 3)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:


Tightly sealed goggles

SECTION 9: Physical and chemical properties
· 9.1 Information on basic physical and chemical properties
· Appearance:

Form: Viscous

Colour: Black

· Odour: Solvent-like

· Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 130 °C

· Flash point: 35 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: > 200 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower: 0.5 Vol %

Upper: 7.0 Vol %

· Oxidising properties Not determined.

· Vapour pressure at 20 °C: 27 hPa

· Density at 20 °C: 0.88 g/cm³

· Relative density Not determined.

· Vapour density Not determined.

· Evaporation rate Not determined.

· Solubility in / Miscibility with water:

Insoluble.

· organic solvents: Miscible with many organic solvents.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: 80 - 115 mm²/s (40 °C)

· Solvent content:

VOC (EC) VOC limit value (cat A/i) 500 g/L 2010.

Product contains 450 g/L.

· 9.2 Other information

No further information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: Stable at environment temperature.

(Contd. on page 5)

Trade name: Wickes - Metal and Concrete Bitumen Paint

(Contd. of page 4)

- **10.3 Possibility of hazardous reactions** Forms flammable gases/fumes.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

hydrocarbons, C9-C11, n-alkanes, isoalkanes cyclic, <2% aromates

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>5000 mg/kg (rab)
--------	------	-------------------

Inhalative	LC50/4 h	>4951 mg/l (rat)
------------	----------	------------------

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)

Oral	LD50	>15000 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>3400 mg/kg (rab)
--------	------	-------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Splashes in the eyes may cause irritation and reversible local damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure**
Causes damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)

EC50	10 mg/l (daphnia)
------	-------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 6)

Trade name: Wickes - Metal and Concrete Bitumen Paint

(Contd. of page 5)

- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN-Number
· ADR, IMDG UN1268
- 14.2 UN proper shipping name
· ADR exemption according 2.2.3.1.5.
UN 1268 PETROLEUM PRODUCTS, N.O.S. (aliphatical white spirit, white spirit)
- IMDG UN 1268, Petroleum products n.o.s., 3, III, (35 °C c.c.)
Transport in accordance with 2.3.2.5 of the IMDG code.
- 14.3 Transport hazard class(es)
· ADR, IMDG
· Class 3 Flammable liquids.
- 14.5 Environmental hazards:
· Marine pollutant: No
- 14.6 Special precautions for user Warning: Flammable liquids.
· EMS Number: F-E,S-E
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.
- Transport/Additional information:
- ADR
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code D/E
- UN "Model Regulation": Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 7)

Trade name: Wickes - Metal and Concrete Bitumen Paint

(Contd. of page 6)

- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57**
This product does not contain any SVHC's.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheet (SDS) is calculated with a Calculation method based on CLP Annex I, parts 2 to 5.

- **Relevant phrases**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

- **Department issuing SDS:** Product safety department

- **Contact:**

Wim Verstraeten

e-mail: Wim.Verstraeten@iko.com

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3