

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** Wickes - Trowel Applied Roofing Felt Adhesive
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
 - SU21 Consumer uses: Private households / general public / consumers
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 - SU19 Building and construction work
- **Application of the substance / the mixture** Bituminous adhesive.
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 - IKO PLC
 - Appley Lane North
 - Appley Bridge
 - Wigan
 - Lancs
 - WN6 9AB
 - technical@ikogroup.co.uk
- **Further information obtainable from:** 01257 256 779, www.ikogroup.co.uk
- **1.4 Emergency telephone number:** +44 (0)1257 256864 Opening Times: 0900 - 1700 Monday to Friday

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
 - Flam. Liq. 3 H226 Flammable liquid and vapour.
 - STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.
 - Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- **Information concerning particular hazards for human and environment:**
 - The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
 - At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.
- **Classification system:**
 - The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008, 453/2010**
 - The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Trade name: Wickes - Trowel Applied Roofing Felt Adhesive

(Contd. of page 1)

Hazard pictograms


GHS02 GHS08 GHS09

Signal word *Danger*
Hazard-determining components of labelling:
Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)
Hazard statements
H226 Flammable liquid and vapour.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
Precautionary statements
P102 Keep out of reach of children.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
Additional information:
EUH066 Repeated exposure may cause skin dryness or cracking.
SECTION 3: Composition/information on ingredients
3.2 Chemical characterization: Mixtures
Description: *Mixture of substances listed below with nonhazardous additions.*
Dangerous components:

EC number: 919-446-0 Reg.nr.: 01-2119458049-33	Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%) Flam. Liq. 3, H226 STOT RE 1, H372; Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H336	15-<25%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H332; STOT SE 3, H335-H336	≤10%

Additional information: *For the wording of the listed/hazard statements refer to section 16.*
SECTION 4: First aid measures
4.1 Description of first aid measures
General information:
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Trade name: **Wickes - Trowel Applied Roofing Felt Adhesive**

(Contd. of page 2)

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Not applicable.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 4)

Trade name: Wickes - Trowel Applied Roofing Felt Adhesive

(Contd. of page 3)

- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Not necessary if room is well-ventilated.
- **Protection of hands:** Solvent resistant gloves
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **Appearance:**
 - Form:** Pasty
 - Colour:** Black
- **Odour:** Solvent-like
- **pH-value:** Not determined.
- **Change in condition**
 - Boiling point/Boiling range:** 135 °C
- **Flash point:** 35 °C
- **Ignition temperature:** > 200 °C
- **Self-igniting:** Product is not selfigniting.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Explosion limits:**
 - Lower:** 0.5 Vol %
 - Upper:** 7.0 Vol %
- **Vapour pressure at 20 °C:** 27 hPa
- **Density at 20 °C:** 0.96 g/cm³
- **Solubility in / Miscibility with water:** Insoluble.
- **organic solvents:** Miscible with many organic solvents.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** 200 - 280 mm²/s (100 °C)
- **Solvent content:**
 - VOC (EC)** VOC limit value (cat A/h) 750 g/L 2010.
Product contains 330 g/L.

(Contd. on page 5)

Trade name: Wickes - Trowel Applied Roofing Felt Adhesive

(Contd. of page 4)

· **9.2 Other information** *No further information available.*

SECTION 10: Stability and reactivity

- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **10.3 Possibility of hazardous reactions** *No dangerous reactions known.*
- **10.4 Conditions to avoid** *No further relevant information available.*
- **10.5 Incompatible materials:** *No further relevant information available.*
- **10.6 Hazardous decomposition products:**
Hazardous decompositions products may be released during prolonged heating like smokes, carbon monoxide and dioxides.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)

Oral	LD50	>15000 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)

Dermal	LD50	>3400 mg/kg (rab)
--------	------	-------------------

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

Dermal	LD50	>2000 mg/kg (rat)
--------	------	-------------------

Inhalative	LC50/4 h	>10.2 mg/l (rat)
------------	----------	------------------

- **Primary irritant effect:**

- **on the skin:**

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

- **on the eye:** *Splashes in the eyes may cause irritation and reversible local damage.*

- **Sensitization:** *No sensitizing effects known.*

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)

EC50	10 mg/l (daphnia)
------	-------------------

64742-95-6 Solvent naphtha (petroleum), light arom.

EC50	≤10 mg/l (daphnia)
------	--------------------

- **12.2 Persistence and degradability** *No further relevant information available.*

- **12.3 Bioaccumulative potential** *No further relevant information available.*

- **12.4 Mobility in soil** *No further relevant information available.*

- **Ecotoxicological effects:**

- **Remark:** *Toxic for fish*

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

(Contd. on page 6)

Trade name: Wickes - Trowel Applied Roofing Felt Adhesive

(Contd. of page 5)



- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- Also poisonous for fish and plankton in water bodies.
- Toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
· **ADR, IMDG** UN1133
- **14.2 UN proper shipping name**
· **ADR** ADHESIVES, 3, III, (D/E), DANGEROUS FOR THE ENVIRONEMENT
· **IMDG** UN 1133, Adhesives, (contains solvent naphta and white spirit mixture),3, III, (35 °C c.c.), MARINE POLLUTANT
- **14.3 Transport hazard class(es)**
· **ADR, IMDG**

 - **Class** 3 Flammable liquids.
 - **Label** 3
- **14.4 Packing group**
· **ADR, IMDG** III
- **14.5 Environmental hazards:** Product contains environmentally hazardous substances: Hydrocarbons, C9-C12, n-alkanes, iso-alkanes, cyclic, aromates (2-25%)
- **Marine pollutant:** Yes
Symbol (fish and tree)
- **Special marking (ADR):** Symbol (fish and tree)
- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Danger code (Kemler):** 30
- **EMS Number:** F-E,S-E
- **14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

(Contd. on page 7)

Trade name: Wickes - Trowel Applied Roofing Felt Adhesive

(Contd. of page 6)

· Transport/Additional information:**· ADR**

- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- **Transport category** 3
- **Tunnel restriction code** D/E

· IMDG

- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":UN1133, ADHESIVES, ENVIRONMENTALLY
HAZARDOUS, 3, III**SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)

- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Flam. Liq. 3: Flammable liquids, Hazard Category 3
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
- STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

(Contd. on page 8)

Trade name: Wickes - Trowel Applied Roofing Felt Adhesive

(Contd. of page 7)

Version History.

Version 1.0 June 23rd 2015 New release for Classification, Labelling Packaging Regulations