


IKOTRIM F

PRODUCT INFORMATION

IKOtrim F, is a roof edge trim, manufactured from GRP (pultruded glass fibre reinforced polyester resin). The trims are thermally inert with a low coefficient of expansion.

Identifier	Product Code
Linear Unit	Refer to product details in Table 1.
Internal Corners	
External Corners	



USE

Thermally inert preformed GRP edge trims for use with reinforced bitumen membrane built up roofing systems.

This product must be installed by an IKO Approved or Registered Installer. All work must be undertaken in accordance with the requirements of the specific information provided with the issued IKO Specification document, or guidance documents where applicable.

FEATURES & BENEFITS

Thermally inert – will not distort or warp with temperature changes.

Maintenance free – no painting required (will not rot or rust) as well as resistant to atmospheric pollution and UV stable.

Lightweight – easily handled, strong and durable.

Simple installation – easily cut and drilled.

COMPOSITION

Material Type:	GRP.
Form:	Pultruded Sections
Colours:	Black/Grey/White
Linear Unit	
Length:	3m
Drip:	65/100/150/200mm
Arm:	60/65/85mm
Corner Units	
Dimension:	240mm x 240mm
Orientation/Angle:	90° Internal/External


INSTALLATION

Secure IKOtrim F Edge Trim, in between the waterproofing underlay and capsheet, mechanically fastened 30mm (max) from the ends at 300mm centre maximum (150mm centres for areas of high wind uplift). Using countersunk screws or suitable fixings (minimum 20mm long) into the sound substrate.

Any trim with a drip length of greater than 150mm **must** also be face fixed with mechanical fixings, to prevent wind uplift.

When fixed the drip should have a 3mm clear gap from wall or fascia.

Prime trim arm with specified primer and install specified detailing capsheet: Pressed into channel of trim.



For further information please refer the IKO Specification Document

DURABILITY

When installed as part of a IKO specified built-up roof system and conditions are maintained as per IKO literature, relevant Codes of Practice and UK Building Regulations, the product will last the period of the IKO specified system guarantee.

Table 1

Code	Product Name	Arm	Drip	Profile
208500BL	IKOtrim F200 85b Black 3M	85mm	200mm	
2085EXBL	IKOtrim F200 85b Black Ext Crn	85mm	200mm	
2085INBL	IKOtrim F200 85b Black Int Crn	85mm	200mm	
WS5566BL	IKOtrim F 6560b Blk 3M	60mm	65mm	
WS5566GR	IKOtrim F 6560g Gry 3M	60mm	65mm	
WS5566WH	IKOtrim F 6560g WHT 3M	60mm	65mm	
WS5568BL	IKOtrim F 10060b BL 3M	60mm	100mm	
WS5568GR	IKOtrim F 10060g GR 3M	60mm	100mm	
WS5568WH	IKOtrim F10060b WHT 3M	60mm	100mm	
WS5570BL	IKOtrim F 15060b BL 3M	60mm	150mm	
WS5570GR	IKOtrim F 15060g GR 3M	60mm	150mm	
WS5570WH	IKOtrim F15060b WHT 3M	60mm	150mm	

DISCLAIMER

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserve the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.