

IKO enertherm MG

Product description:

IKO enertherm MG is a 100 % CFC, HCFC, and HFC-free insulation board with a core in hard polyisocyanurate foam, laminated on both sides with a perforated coated glass fabric.

Application:

Roof: Flat roof insulation for use with bitumen, mastic asphalt, single-ply or or adhesive bonded waterproofing systems.



Edge finish:

 Straight

Thermal performance:

Thermal conductivity: (EN 13165) λ_D : **0,027 W/(m.K)** untill 120 mm, **0,026 W/(m.K)** from 120 mm.

Technical details:

Bulk density: \pm **32 kg/m³**

Compressive strength at 10% deformation: \geq **150 kPa (15 ton/m²)**

Behaviour under uniformly distributed loading: **Class C** (\leq 5 % deformation at 80 °C and 40 kPa loading)

Closed cells: **more than 95%**

Water vapour diffusion resistance: PIR foam: μ = **60** - lamination: μ > **100**

Fire properties

Fire class to EN 13501-1: **Class E**

Technical approvals:

UKCA: BS/EN 13165: T2-DS(70,90)3-DS (-20,-)1-DLT(2)5-TR80-CS(10Y)150-WL(T)1

Availability:

Thickness (mm)		30	40	50	60	70	81	90	100	120	140
1 200 x 1 000	m2/pack	19,20	14,40	-	9,60	-	7,20	-	6,00	4,80	3,6
	m2/pal	96,00	72,00	-	42,00	-	36,00	-	30,00	24,00	21,60

Pack height: max 500 mm, pallet height: maximaal 2600 mm (incl. 100 mm feet).