

**IKO ULTRA PREVENT 25**

**PRODUCT INFORMATION**

**IKO Ultra Prevent 25** is a fully bonded torch-applied, polyester reinforced, SBS modified bitumen capsheet with added fire retardant. It has an upper surface finish of mineral granules and a thermo-fusible film on the underside.



Colour	Product Code
Brown	66950000
Black	66951000
Green	66940000

**USE**

This product is for use as a capsheet layer within an IKO high performance built up roofing system specification.

The product must be applied by an IKO Approved Installer. All work must be undertaken in accordance with the requirements of the specific information provided with the issued IKO Specification document, or guidance documents where applicable.

**INDEPENDENT ACCREDITATION**



The product carries a Declaration of Performance Certificate, Agreement Certificate 91/2671, and is UK Conformity Assessed.

**FEATURES & BENEFITS**

**High Performance** – Exceptional dimensional stability and tensile strength.

**Fire Performance** – Incorporates Prevent Graphite Fire Wall Technology with self-extinguishing properties.

**High Specification** – Forms part of an IKO flat roofing specification offer.

**COMPOSITION**

<b>Bitumen Modification:</b>	SBS
<b>Carrier:</b>	Polyester
<b>Form:</b>	Roll
<b>Colour:</b>	Brown/ Black/ Green
<b>Length:</b>	8m
<b>Width:</b>	1m
<b>Mass/Weight:</b>	5kg/m <sup>2</sup>
<b>Roll Weight:</b>	40kg
<b>Surface Finishes:</b>	(upper) Mineral (lower) Thermo-fusible film
<b>Selvedge:</b>	(upper) 75mm

**INSTALLATION**

<b>Membrane Bond:</b>	Torch applied
<b>Lap Bond:</b>	Torch applied

**PERFORMANCE**

For key product performance characteristics, please refer to the [IKO Declaration of Performance \(DoP\)](#)

**DISCLAIMER**

As this product is utilised within an Approved Contractor network and guided by an IKO Specification document, where omission or differing information exists the IKO Specification document will take precedence.

Mineral coated cap sheets -  
A mineral coated cap sheet will, to some extent and through its lifetime, shed some mineral. During the roofing membrane manufacturing process, mineral is applied into the hot top coating of bitumen. An excessive amount of mineral is used to provide total and complete coverage of the roll and the loose granule will naturally fall away after installation.

**Batch colour variations -**

The mineral is a natural product and at times there may be a shade variation, this does not affect the waterproofing quality or the performance of the waterproofing membrane.

Once the membrane has been installed IKO will not be held liable for any such claims regarding colour variations and mineral loss, unless proven by IKO to be a product failure.

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserve the right to amend and/or withdraw this document without notice. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.