

## IKO HYLOAD TRADE DPC

### PRODUCT INFORMATION

A flexible polymeric sheet material, used within sold/cavity walls to prevent passage of moisture from the ground and at all levels when formed into a cavity tray profile to prevent the downward movement of water.

Roll Width	Product Code
100mm - 1m	316****



### USE

IKO Hyload Trade DPC is used as a horizontal, vertical or stepped damp proof coursing system and is also suitable for the on-site creation of cavity trays within cavity wall construction.

### INDEPENDENT ACCREDITATION



CPR-14909-A



CPR-14909-A



The product carries a Declaration of Performance Certificate, Agrément Certificate 95/3133, and is UK Conformity Assessed.

### FEATURES & BENEFITS

#### Developed Components

As part of the IKO Hyload system, the product has a full range of components.

#### Excellent under Compressive Load

The system does not extrude under load, under normal working conditions.

#### Robust

Excellent resistance to impact damage, under normal working conditions.

### COMPOSITION

<b>Material:</b>	Polymeric
<b>Form:</b>	Roll
<b>Colour:</b>	Black
<b>Thickness:</b>	0.9mm
<b>Weight:</b>	1.26kg/m <sup>2</sup>
<b>Roll Length:</b>	20m
<b>Roll Width:</b>	100mm – 1000mm
<b>Surface Finishes:</b>	(upper) Grained (lower) Grained
<b>Selvage:</b>	None

### INSTALLATION

<b>Membrane Bond:</b>	Loose Laid
<b>Lap Bond:</b>	Taped

For further information please refer the 'IKO Hyload DPC System Guidance Document'

### PERFORMANCE

For key product performance characteristics, please refer to the [IKO Declaration of Performance \(DoP\)](#)

### DURABILITY

When properly specified and installed, the system in normal circumstances, will remain effective for the lifetime of the building.

## **DISCLAIMER**

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. IKO reserve the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.