

IKO EAVES PROTECTION STRIP

PRODUCT INFORMATION

IKO Eaves Protection Strip is a width of polyester reinforced bitumen membrane that is designed to give long term protection when dressing an under slating membrane into an external gutter.

Width	Product Code
330mm	04051610
500mm	04051600



USE

IKO Eaves Protection Strip is fixed as the first sheet along the eaves, so it can be subsequently dressed over and inside the edge of the external gutter. The main underslating membrane should then be laid to lap with this product.

INDEPENDENT ACCREDITATION



2797-CPR-537586



0086-CPR-745786

The product carries a Declaration of Performance Certificate and is UK Conformity Assessed.

FEATURES & BENEFITS

Universal – can be used with both high and low vapour resistance membranes.

Robust – the polyester carrier gives the material an increased rot resistance over other types of underslating membrane.

Longevity - life expectancy commensurate to the main roof underslating membrane.

Width options – available in two widths to meet project specific requirements.

COMPOSITION

Bitumen Modification:	Oxidised
Form:	Roll
Carrier:	Polyester
Roll Length:	16m
Roll Width:	330mm/500mm
Roll Weight:	10kg/14.5kg

PERFORMANCE

For key product performance characteristics, please refer to the [IKO Declaration of Performance \(DoP\)](#)

CONSTRUCTION

MATERIAL HANDLING

Checking: Material should be checked to ensure that they conform to the project specification.

Handling: Material should be unloaded and handled with care to avoid damage.

Site Storage: Material should be stored on end on a firm, clean base protected from direct sunlight.

PRIOR TO COMMENCEMENT

Application must always follow good, safe working practice. Prior to commencing works, it is advisable to consult Health and Safety Executive Guidance documents such as HSG33 'Health and Safety in Roof Work', irrespective of levels of competence, to ensure all works are being planned and undertaken in a safe, pragmatic manner.

GENERAL FIXING

Work should commence with the installation of **IKO Eaves Protection Strip**, laid parallel to the eaves and fixed with clout nails to every rafter 25mm from the top edge. The bottom edge should be dressed and detailed over the fascia, eaves support board and tilt fillets into the externally mounted gutter position, a minimum material overhang of 50mm or to the centre line of the gutter system is desirable. Do not allow the material to sit in direct contact with the gutter as this may obstruct water flow.



DURABILITY

When installed and conditions are maintained as per IKO literature, relevant Codes of Practice and UK Building Regulations, the product will have a life expectancy commensurate to the main roof underslating membrane.

DISCLAIMER

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded. IKO reserve the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.