

IKO ULTRA Prevent 25 Torch-On Capsheet

Technical Data Sheet

PRODUCT INFORMATION

IKO ULTRA Prevent 25 is a fully bonded torch-applied, polyester reinforced, SBS modified bitumen capsheet with added fire retardant. It has an upper surface finish of mineral granules and a thermo-fusible film on the underside

This product is for use as a capsheet layer within an IKO high performance built up roofing system specification.

The product must be applied by an IKO Approved Installer. All work must be undertaken in accordance with the requirements of the specific information provided with the issued IKO Specification document, or guidance documents where applicable

| Colour | Product Code |
|--------|--------------|
| Brown | 66950000 |
| Black | 66951000 |
| Green | 66940000 |

| | |
|------------------------------|---|
| Bitumen Modification | SBS |
| Carrier | Polyester |
| Form | Roll |
| Measurements | 8m (length) x 1m (width) |
| Mass/Weight | 5kg/m ² |
| Roll Weight | 40kg |
| Surface Finishes | Mineral (upper) - Thermo-fusible film (lower) |
| Selvedge | 75mm |
| Installation – Membrane Bond | Torch Applied |
| Installation – Lap Bond | Torch Applied |

FEATURES & BENEFITS

- High Performance – Exceptional dimensional stability and tensile strength.
- Fire Performance – Incorporates Prevent Graphite Fire Wall Technology with self-extinguishing properties.
- High Specification – Forms part of an IKO flat roofing specification offer.

PRODUCT ACCREDITATIONS



The product carries a Declaration of Performance Certificate, Agreement Certificate 91/2671, and is UK Conformity Assessed.

INSTALLATION GUIDELINES

For further information on installation and guidance this is available upon request and can be downloaded [here](#)

HEALTH & SAFETY

Material Safety Data Sheets are available upon request and can be downloaded from:
ikogroup.co.uk/resource-centre/

TECHNICAL SUPPORT

Advice is available from IKO Technical Services:
Telephone: 01257 255771
Email: technical.ab@iko.com

ACCREDITATIONS



Appley Lane North
Appley Bridge
Wigan
WN6 9AB

Coney Green Road
Clay Cross
Chesterfield
S45 9HZ

Prospect Quarry
Grangemill
Matlock
DE4 4BW

t: 01257 255771
e: getintouch.uk@iko.com



DISCLAIMER

As this product is utilised within an Approved Contractor network and guided by an IKO Specification document, where omission or differing information exists the IKO Specification document will take precedence.

Mineral coated cap sheets –

A mineral coated cap sheet will, to some extent and through its lifetime, shed some mineral. During the roofing membrane manufacturing process, mineral is applied into the hot top coating of bitumen. An excessive amount of mineral is used to provide total and complete coverage of the roll and the loose granule will naturally fall away after installation.

Batch colour variations -

The mineral is a natural product and at times there may be a shade variation, this does not affect the waterproofing quality or the performance of the waterproofing membrane.

Once the membrane has been installed IKO will not be held liable for any such claims regarding colour variations and mineral loss, unless proven by IKO to be a product failure.

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserve the right to amend and/or withdraw this document without notice. Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued

Appley Lane North
Appley Bridge
Wigan
WN6 9AB

Coney Green Road
Clay Cross
Chesterfield
S45 9HZ

Prospect Quarry
Grangemill
Matlock
DE4 4BW

t: 01257 255771
e: getintouch.uk@iko.com

