

IKO Spectraplan TPE Contact Adhesive

Technical Data Sheet

PRODUCT INFORMATION

IKO Spectraplan TPE Contact Adhesive is a ready to use contact adhesive for adhering IKO Spectraplan SM and D membrane to various tested substrates.

IKO Spectraplan Membrane Coated Metal Sizes

IKO product code	30340350
Colour	Yellow
Storage	Dry, away from ignition sources 8-25°C
Shelf life:	(Unopened 8-25°C) 12 months
Application Temperature:	(approx.) 8-30°C
Coverage:	(approx.) 150gr/m ² per surface

FEATURES & BENEFITS

- Superior Adhesion: Ensures a strong and durable bond.
- Cold Application: Easy to apply with a brush or roller.
- Rapid Installation
- Cost-effective roofing systems only installed by approved contractors.

HEALTH & SAFETY

Material Safety Data Sheets are available upon request and can be downloaded from:

ikogroup.co.uk/resource-centre/

TECHNICAL SUPPORT

Advice is available from IKO Technical Services:

Telephone: 01257 255771

Email: technical.cc@iko.com

Appley Lane North
Appley Bridge
Wigan
WN6 9AB

Coney Green Road
Clay Cross
Chesterfield
S45 9HZ

Prospect Quarry
Grangemill
Matlock
DE4 4BW

t: 01257 255771
e: getintouch.uk@iko.com



ACCREDITATIONS



DISCLAIMER

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserves the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.

Appley Lane North
Appley Bridge
Wigan
WN6 9AB

Coney Green Road
Clay Cross
Chesterfield
S45 9HZ

Prospect Quarry
Grangemill
Matlock
DE4 4BW

t: 01257 255771
e: getintouch.uk@iko.com

