

POLYETHYLENE VAPOUR CONTROL LAYER

PRODUCT INFORMATION

Spectravap is a 0.3mm thick polyethylene vapour control layer (VCL), suitable for use on most IKO Polymeric mechanically fastened systems.

Product	Spectravap
Roll Weight	30.0 Kg
Thickness	0.3 mm
Roll Dimensions	25 x 4m
Material	Polyethylene
Moisture Vapour Resistance	>600 MNs/g
Product Code	30833600
Product	Spectravap

FEATURES & BENEFITS

- Cost Effective
- Rapid Installation
- Cold application



SPECTRAVAP APPLICATION

Spectravap is loose laid over the substrate.

Overlap side and end laps by a minimum of 150mm and seal with Spectravap jointing tape.

At parapets and upstands the VCL must be carried to the upper edge of the thermal insulation and sealed to the upstand or penetration with Spectravap jointing tape.

When installed vertically Spectravap must be mechanically secured along the top edge.

On rough surfaces a layer of Spectratex geotextile should be used as a cushion layer before installing the Spectravap VCL.

STORAGE

Spectravap should be stored on a clean level surface away from excessive heat and under cover.

FURTHER PRODUCT INFORMATION

Full product literature, health & safety and technical sheets are available as downloads from our website www.ikopolymeric.com or on request by email polymeric.marketing@iko.com.