

# IKO Eaves Protection Strip

## Technical Data Sheet – Section 2.30

### PRODUCT INFORMATION

IKO Eaves Protection Strip is a width of polyester reinforced bitumen membrane that is designed to give long term protection when dressing an under slating membrane into an external gutter.

Width	Product Code
330mm	04051610
500mm	04051600



### USE

IKO Eaves Protection Strip is fixed as the first sheet along the eaves, so it can be subsequently dressed over and inside the edge of the external gutter. The main under slating membrane should then be laid to lap with this product.

### INDEPENDENT ACCREDITATION



2797-CPR-537586



0086-CPR-745786

The product carries a Declaration of Performance Certificate and is UK Conformity Assessed.

### FEATURES & BENEFITS

Universal - Can be used with both high and low vapour resistance membranes.

Robust - The polyester carrier gives the material an increased rot resistance over other types of under slating membrane.

Longevity - Life expectancy commensurate to the main roof under slating membrane.

Width options - Available in two widths to meet project specific requirements.

### COMPOSITION

Bitumen Modification:	Oxidised
Form:	Roll
Carrier:	Polyester
Roll Length:	16m
Roll Width:	330mm/500mm
Roll Weight:	10kg/14.5kg

## **PERFORMANCE**

For key product performance characteristics, please refer to the IKO Declaration of Performance (DoP)

## **CONSTRUCTION**

### **Material Handling**

Checking: Material should be checked to ensure that they conform to the project specification.

Handling: Material should be unloaded and handled with care to avoid damage.

Site Storage: Material should be stored on end on a firm, clean base protected from direct sunlight.

### **Prior to Commencement**

Application must always follow good, safe working practice. Prior to commencing works, it is advisable to consult Health and Safety Executive Guidance documents such as HSG33 'Health and Safety in Roof Work', irrespective of levels of competence, to ensure all works are being planned and undertaken in a safe, pragmatic manner.

### **General Fixing**

Work should commence with the installation of IKO Eaves Protection Strip, laid parallel to the eaves and fixed with clout nails to every rafter 25mm from the top edge. The bottom edge should be dressed and detailed over the fascia, eaves support board and tilt fillets into the externally mounted gutter position, a minimum material overhang of 50mm or to the centre line of the gutter system is desirable. Do not allow the material to sit in direct contact with the gutter as this may obstruct water flow.



## **DURABILITY**

When installed and conditions are maintained as per IKO literature, relevant Codes of Practice and UK Building Regulations, the product will have a life expectancy commensurate to the main roof under slating membrane.

## **OTHER RELEVANT DOCUMENTATION**

Where applicable, Material Safety Data Sheets (MSDS), Declaration of Performances (DoPs), and Third-Party Accreditations are available to view and download from the IKO website Resource Centre:

<https://ikogroup.co.uk/resource-centre/>

## **PRODUCT SUPPORT**

Should you have any queries in relation to this product please contact one of the relevant teams below:

<b>Technical</b>	<a href="mailto:technical.ab@iko.com">technical.ab@iko.com</a> <ul style="list-style-type: none"><li>- For Reinforced Bitumen Membranes, IKOpro and Flexia Liquid Applied Waterproofing, Pitched Roofing, IKO Hyload Structural Waterproofing</li></ul> <a href="mailto:technical.ma@iko.com">technical.ma@iko.com</a> <ul style="list-style-type: none"><li>- For Mastic Asphalt</li></ul> <a href="mailto:technical.cc@iko.com">technical.cc@iko.com</a> <ul style="list-style-type: none"><li>- For Single Ply and Permatec Hot Melt</li></ul>
<b>Sales</b>	<a href="mailto:sales.uk@iko.com">sales.uk@iko.com</a>
<b>Marketing</b>	<a href="mailto:getintouch.uk@iko.com">getintouch.uk@iko.com</a>

## **COMPANY ACCREDITATIONS**

IKO PLC, a roofing, waterproofing, and insulation company, holds various accreditations that demonstrate its commitment to quality, safety, and environmental responsibility. These include ISO certifications for quality management and occupational health and safety, British Board of Agrément (BBA) accreditations for specific products and systems, and Factory Mutual (FM) approval for certain roofing systems.

All our manufacturing plants have BS EN ISO 9001, BS EN ISO 14001, BS EN ISO 45001, and BES 6001 accreditation, meaning we match the quality and sustainability requirements and use responsibly sourced raw materials in our production. We also re-use by-products from manufacture, wrap products in minimal packaging, and we employ a streamlined transportation network.



IKO is also a leading member of all relevant trade associations such as NFRC, BFRA, SPRA, LRWA, MAC, RSTA, BJA and LCRIG having technical experts within the technical and standards committees to help us get informed first-hand about recent updates on technical requirements for the design and installation of roofing, waterproofing, road and bridge maintenance industry products.



## **DISCLAIMER**

Whilst every precaution is taken to ensure that the information given in this literature is correct and up-to-date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserves the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was published.