SECTION 6.2 BUFR COMMODITY



Technical Data Sheet

August 2025

IKO FILM ON FILM SBS T-O UNDERLAY

PRODUCT INFORMATION

A fully bonded torch-applied, glass fibre reinforced, SBS modified bitumen underlay. It is finished on both sides with a thermo-fusible film.

Surface	Product Code
Thermo-fusible Film	58460000



USE

product is intended for use underlay/intermediate layer within a bituminous builtup roofing system.

INDEPENDENT ACCREDITATION





2797-CPR-537586

The product carries a Declaration of Performance Certificate and is UK Conformity Assessed.

FEATURES & BENEFITS

Torch-applied

Can be applied all year round as less affected by weather/ temperature variations.

Can be considered for use within a torch-applied system overlaying existing bitumen roofing.

Glass Fibre Reinforced Carrier

Provides an economical base material.

SBS Modified Bitumen

Retains excellent flexibility under ambient temperature fluctuations for enhanced system longevity.

Thermo-fusible Film Finish

Provides bitumen-to-bitumen contact during application of the cap sheet for excellent adhesion.

COMPOSITION

Bitumen Modification: SBS

Carrier: Glass Fibre

Form: Roll Colour: Black Length: 16m Width: 1m Mass/Weight: 2.4kg/m² **Roll Weight:** 38.4kg

Surface Finishes: (upper) Thermo-Fusible Film

(lower) Thermo-Fusible Film

Selvedge: None

INSTALLATION

Membrane Bond: Torch-applied Torch-applied Lap Bond:

For further information please refer the 'IKO BUFR System Guidance Document'

PERFORMANCE

For key product performance characteristics, please refer to the IKO Declaration of Performance (DoP)

DURABILITY

When installed and conditions are maintained as per IKO literature, relevant Codes of Practice and UK Building Regulations, the product will contribute to the durability stated by the respective cap sheet.

DISCLAIMER

Whilst every precaution is taken to ensure that the information given in this literature is correct and up to date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserve the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was issued.