

IKOpro Stickall

Technical Data Sheet – Section 11.00

PRODUCT INFORMATION

IKOpro Stickall is a dense elastomer modified bituminous sealant, adhering well to most building surfaces.

Pack Size	Product Code
310ml	2401671

USE

A bituminous mastic sealant, typically used for the pointing of lead-free flashings such as IKO Flash.

APPEARANCE & PERFORMANCE

Appearance:	Viscous Liquid
Colour:	Black
Size:	310ml
Weight:	500g
Use:	Adhesive
Coverage*:	3 linear metres
Application Temperature:	5-30°C
Shelf Life**:	3 years

* Based on a uniform 10mm² bead

** In sealed packaging

CONSTRUCTION

MATERIAL HANDLING

Please refer to relevant sections of the IKO Material Safety Data Sheet.

PRIOR TO COMMENCEMENT

Application must always follow good, safe working practice. Prior to commencing works, it is important that operatives read the IKO Material Safety Data Sheet. Additionally, it is important to be aware of all the information given by your employers Risk Assessments and understand all Method Statements produced for undertaking the work.

PREPARATION

Before commencement, the user should ensure that the receiving surfaces are sound and capable of accepting the product. Material and/or substrates should be checked for compatibility and if necessary assessed by a competent person to ascertain their suitability for bonding.



APPLICATION

Product is applied using a 310ml sized sealant gun. Prior to installing the nozzle, the cartridge tip should be cut to ensure free flow of material from cartridge into the nozzle. The nozzle should be cut to the desired bead thickness.

POST COMPLETION

Information regarding disposal of empty containers or containers with residual liquid can be found within the relevant sections of the IKO Material Safety Data Sheet.

OTHER RELEVANT DOCUMENTATION

Where applicable, Material Safety Data Sheets (MSDS), Declaration of Performances (DoPs), and Third-Party Accreditations are available to view and download from the IKO website Resource Centre:

<https://ikogroup.co.uk/resource-centre/>

PRODUCT SUPPORT

Should you have any queries in relation to this product please contact one of the relevant teams below:

Technical technical.ab@iko.com

- For Reinforced Bitumen Membranes, IKOpro and Flexia Liquid Applied Waterproofing, Pitched Roofing, IKO Hyload Structural Waterproofing

technical.ma@iko.com

- For Mastic Asphalt

technical.cc@iko.com

- For Single Ply and Permasec Hot Melt

Sales sales.uk@iko.com

Marketing getintouch.uk@iko.com

COMPANY ACCREDITATIONS

IKO PLC, a roofing, waterproofing, and insulation company, holds various accreditations that demonstrate its commitment to quality, safety, and environmental responsibility. These include ISO certifications for quality management and occupational health and safety, British Board of Agrément (BBA) accreditations for specific products and systems, and Factory Mutual (FM) approval for certain roofing systems.

All our manufacturing plants have BS EN ISO 9001, BS EN ISO 14001, BS EN ISO 45001, and BES 6001 accreditation, meaning we match the quality and sustainability requirements and use responsibly sourced raw materials in our production. We also re-use by-products from manufacture, wrap products in minimal packaging, and we employ a streamlined transportation network.



IKO is also a leading member of all relevant trade associations such as NFRC, BFRA, SPRA, LRWA, MAC, RSTA, BJA and LCRIG having technical experts within the technical and standards committees to help us get informed first-hand about recent updates on technical requirements for the design and installation of roofing, waterproofing, road and bridge maintenance industry products.



DISCLAIMER

Whilst every precaution is taken to ensure that the information given in this literature is correct and up-to-date it is not intended to form part of any contract or give rise to any collateral liability, which is hereby specifically excluded.

IKO reserves the right to amend and/or withdraw this document without notice.

Intending purchasers of our materials should therefore verify with the company whether any changes in our specification, application details, withdrawals or otherwise have taken place since this literature was published.