

IKO enertherm BM

Product description:

IKO enertherm BM is a 100 % CFC, HCFC or HFC free insulation board with a core of hard Polyisocyanurate foam, laminated on one side with polypropylene coated bituminised sand and talc free glass fibre and on the other side with perforated coated glass fibre. To install bitumen roofing sections using a flame torch: bituminised sand and talc free glass fibre to be applied facing upwards. With synthetic roof sections: perforated coated glass fibre to be applied facing upwards.

Application:

Roof: Flat roof insulation for use with torch-applied bituminous roofing



Edge finish:

 Straight

Thermal performance:

Thermal conductivity: (EN 13165) λ_D : **0,026 W/(m.K)** until 120 mm and **0,025 W/(m.K)** from 120 mm.

Technical details:

Compressive strength at 10 % deformation: **≥ 150 kPa (15 ton/m²)**

Behaviour under uniformly distributed loading: (≤ 5 % deformation at 80 °C and 40 kPa loading)

Closed cells: **more than 95%**

Water vapour diffusion resistance: PIR foam: $\mu = 60$ - lamination: $\mu > 100$

Fire properties

Fire class to EN 13501-1: **F**

Technical approvals:

UKCA: BS/EN 13165: T2-DS(TH)8-DLT(2)5-TR80-CS(10/Y)150-WL(T)1

Availability:

Thickness (mm) Rd (m ² .K/W)		30 1,15	40 1,50	50 1,90	60 2,30	81 3,10	100 3,80	120 4,80	140 5,60
1200 x 600	m ² /pac	11,52	8,64	7,20	5,76	4,32	3,60	2,88	2,16
	m ² /pal	115,20	86,40	72,00	57,60	43,20	36,00	28,80	25,92

Pack height: max 500 mm, pallet height: maximum 2,600 mm (incl. 100 mm feet).